VPDES PERMIT NO. VA0065552

OPEQUON WATER RECLAMATION FACILITY

APPLICATION FOR REISSUANCE OF DISCHARGE PERMIT

# MEMORANDUM

# DEPARTMENT OF ENVIRONMENTAL QUALITY

# VALLEY REGIONAL OFFICE

4411 Early Roa	ad - P.O. Box 3000 Harrisonburg, VA 22801
SUBJECT:	Application Errata for the Opequon Water Reclamation Facility, Reissuance, VA0065552, Frederick County
TO:	PP File
FROM:	PP File Trevor Wallace
DATE:	September 7, 2010
The following of	deficiencies were noted in the subject permit application:
	N ADDENDUM acility is not with town boundaries.
	sed O&M Manual will be needed for the upgraded and expanded facility. The previous permit broval date is also the most recent Sludge/Solids Management Plan approval date.
	A e applicant submitted a waiver request for reporting oil and grease and TDS. The justification is ne waiver acceptable.
conducting a co	opplicant submitted a waiver request for reporting these parameters. The permittee will be complete WQS parameter scan in accordance with their permit once the expanded 12.6 MGD facility ithin the next year. The justification is adequate and the waiver acceptable.
	AGE SLUDGE APPLICATION FORM as 2,4,5,6,7,8 & 9 – No responses provided. Should indicate "N/A"
Section B, Item	6.a Class A is indicated, but should be listed as Class B.
Reviewer Conc	currence:

# Frederick-Winchester Service Authority

Post Office Box 43 Winchester, Virginia 22604

Office: 107 North Kent Street County Office Complex Winchester, Virginia 22601 1-540-722-3579

August 17, 2010

Trevor Wallace Environmental Engineer Virginia Department of Environmental Quality Valley Regional Office 4411 Early Road P.O. Box 3000 Harrisonburg, VA 22801 AUG 23 2010

Dear Mr. Wallace:

Reference:

Reissuance of VPDES Permit No. VA0065552 Opequon Water Reclamation Facility

Please find enclosed a completed application for reissuance of the above-mentioned discharge permit issued to the Frederick-Winchester Service Authority for the Opequon Water Reclamation Facility. We have assembled the application into four sections.

- Section1 titled Form 2A which contains the "Basic Application Information" Parts A, B and C.
- Section 2 titled Part D, E, & F which contains supplementary information on effluent testing data, toxicity monitoring data, and industrial users related to the Opequon Facility. Please note that we have included a request to waive the effluent testing data requesting in Part D.
- Section 3 titled Sludge Permit which contains information regarding processing, testing and disposal of sludge produced at the Opequon Facility.
- Section 4 titled Other Forms which contains VPDES Permit Application Addendum, Permit Billing Information Form and Public Notice Billing Information Form.

We have attempted to reduce the size of the application package by making references where possible to data provided to DEQ through other periodic testing reports that we have provided with DMR reports through the prior permitting period of June 2006 to this date.

Sincerely

Jesse W. Moffett Executive Director

Frederick-Winchester Service Authority

Day 3 "Maintaining and Promoting the Values of the Community through Environmental Stewardship"

# SECTION 1

FORM 2A

"BASIC APPLICATION INFORMATION"

PARTS A, B AND C

Opequon Water Reclamation Facility VA0065552

FORM 2A

# NPDES FORM 2A APPLICATION OVERVIEW

NPDES

#### APPLICATION OVERVIEW

Form 2A has been developed in a modular format and consists of a "Basic Application Information" packet and a "Supplemental Application Information" packet. The Basic Application Information packet is divided into two parts. All applicants must complete Parts A and C. Applicants with a design flow greater than or equal to 0.1 mgd must also complete Part B. Some applicants must also complete the Supplemental Application Information packet. The following items explain which parts of Form 2A you must complete.

Form Approved 1/14/99

OMB Number 2040-0086

# **BASIC APPLICATION INFORMATION:**

- A. Basic Application Information for all Applicants. All applicants must complete questions A.1 through A.8. A treatment works that discharges effluent to surface waters of the United States must also answer questions A.9 through A.12.
- B. Additional Application Information for Applicants with a Design Flow ≥ 0.1 mgd. All treatment works that have design flows greater than or equal to 0.1 million gallons per day must complete questions B.1 through B.6.
- C. Certification. All applicants must complete Part C (Certification).

### SUPPLEMENTAL APPLICATION INFORMATION:

- D. Expanded Effluent Testing Data. A treatment works that discharges effluent to surface waters of the United States and meets one or more of the following criteria must complete Part D (Expanded Effluent Testing Data):
  - 1. Has a design flow rate greater than or equal to 1 mgd,
  - 2. Is required to have a pretreatment program (or has one in place), or
  - 3. Is otherwise required by the permitting authority to provide the information.
- E. Toxicity Testing Data. A treatment works that meets one or more of the following criteria must complete Part E (Toxicity Testing Data):
  - 1. Has a design flow rate greater than or equal to 1 mgd,
  - 2. Is required to have a pretreatment program (or has one in place), or
  - 3. Is otherwise required by the permitting authority to submit results of toxicity testing.
- F. Industrial User Discharges and RCRA/CERCLA Wastes. A treatment works that accepts process wastewater from any significant industrial users (SIUs) or receives RCRA or CERCLA wastes must complete Part F (Industrial User Discharges and RCRA/CERCLA Wastes). SIUs are defined as:
  - 1. All industrial users subject to Categorical Pretreatment Standards under 40 Code of Federal Regulations (CFR) 403.6 and 40 CFR Chapter I, Subchapter N (see instructions); and
  - 2. Any other industrial user that:
    - a. Discharges an average of 25,000 gallons per day or more of process wastewater to the treatment works (with certain exclusions): or
    - b. Contributes a process wastestream that makes up 5 percent or more of the average dry weather hydraulic or organic capacity of the treatment plant; or
    - c. Is designated as an SIU by the control authority.
- G. Combined Sewer Systems. A treatment works that has a combined sewer system must complete Part G (Combined Sewer Systems).

# ALL APPLICANTS MUST COMPLETE PART C (CERTIFICATION)

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22. Page 1 of 21



ВА	SIC APPLICA	TION INFO	ORMATION			
PAF	TA. BASIC APP	LICATION INF	ORMATION FOR ALL	APPLICANTS:		e de la companya de l
All tı	eatment works mus	st complete que	stions A.1 through A.8 of	this Basic Application Information pa	cket	
A,1.	Facility Informatio	n.				70 f 1
	Facility name	Opequon Wa	ater Reclamation Facility			20 Miles
	Mailing Address	3100 Berryvi Winchester,	lle Pike			ika en la esta je estresa ete sistema e
	Contact person	Mr. Donald F	Riggleman			A D. C. and an I Commission of the A. Marine
	Title	Facility Mana	ager			
	Telephone number	(540) 665-98	67			VI TONIA NA TATA MANAGAMANA
	Facility Address	3100 Berryvil	le Pike			Y
	(not P.O. Box)	Winchester, \				A Property of the Control of the Con
A.2.	Applicant Informat	i <b>on.</b> If the applic	cant is different from the abo	ove, provide the following:		
	Applicant name	Frederick-Wi	nchester Service Author	ítv		
	Mailing Address					:
	Maiming Address	P.O. Box 43 Winchester, \				
	Contact person	Jesse W. Mo	<b>€</b> 0++			:
	•				AND CONTRACTOR OF THE PROPERTY	
	Title	Executive Dir	ector			
	Telephone number	(540) 722-35	79			
	1	owner or opera	ator (or both) of the treatn	nent works?		
	owner		operator	distributed to the Constitution of the constitution of		
	Indicate whether co	rrespondence reg	garding this permit should b applicant	e directed to the facility or the applicant.		
		***************************************	area.	of an animal and the the	at house been increased to the treatment	
A.J.	works (include state	ental Permits. r -issued permits).	-rovide the permit number (	of any existing environmental permits tha	a have been issued to the deathert	
	NPDES <u>VA0065</u>	552		PSD		
	UIC			Other		
	RCRA			Other		
A.4.	Collection System each entity and, if keetc.).	Information. Processing Provide inf	ovide information on munic ormation on the type of coll	ipalities and areas served by the facility. ection system (combined vs. separate) a	Provide the name and population of and its ownership (municipal, private,	
	Name		Population Served	Type of Collection System	Ownership	
	Frederick County		23,400	Separate	Municipal	
	City of Wincheste	r	25,200	Separate	<u>Municipal</u>	
	Tatal na	pulation served	48 600			
	rotai po	pulation served	40,000			

	ILITY NAME AND PERMIT NUMBER: Juon Water Reclamation Facility VA00	065552	19-44 b 19-19-19-19-19-19-19-19-19-19-19-19-19-1			rm Approved 1/ viB Number 204	
5.	Indian Country.	AND					
	a. Is the treatment works located in Indi	an Country?					
	Yes	, No					
	b. Does the treatment works discharge through) Indian Country?	to a recelving water that is eith	ner in Indian Country	or that is ups	stream from (a	nd eventually	flows
	Yes	No					
	Flow. Indicate the design flow rate of the average daily flow rate and maximum da period with the 12th month of "this year"	ly flow rate for each of the last	three years. Each y	ear's data m	ust be based	lle). Also prov on a 12-month	ride the i time
	a. Design flow rate12.6	mgd .					
		Two Years Ago	Last Year		This Year		
	b. Annual average daily flow rate	6.386		6.695	\	7.574	mgd
	c. Maximum daily flow rate	19.8		17.38		22.42	mgd
	Collection System. Indicate the type(s) contribution (by miles) of each.	of collection system(s) used b	y the treatment plant	. Check all t	hat apply. Als	o estimate the	percei
	Separate sanitary sewer					100	%
	Combined storm and sanitary s	ewer					%
8.	Discharges and Other Disposal Metho	ds.					
	Does the treatment works discharge	effluent to waters of the U.S.?		✓	Yes		No
	If yes, list how many of each of the fo		ots the treatment wor	ks uses:			
	Discharges of treated effluent				1		
	ii. Discharges of untreated or partia	lly treated effluent			0		
	iii. Combined sewer overflow points	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			0		
	iv. Constructed emergency overflow	s (prior to the headworks)			0		
	<b>.</b>	(p.10) to the toucher,			0	······································	
	V. Other				<u></u>		
	b. Does the treatment works discharge impoundments that do not have outle	effluent to basins, ponds, or ot ts for discharge to waters of th	her surface e U.S.?	**************************************	Yes		No
	If yes, provide the following for each.  Location:	surface impoundment:	Charitana				- ALIAN BENTAN
	Annual average daily volume dischar	ged to surface impoundment(s	3)	·		mgd	
	Is discharge continuo	us or intermitter	nt?				
,	c. Does the treatment works land-apply	treated wastewater?		***************************************	Yes		No
	If yes, provide the following for each:	and application site:					
	Location:						
	Annual average daily volume applied			<b>1</b> gd			
	Is land application co		mittent?				
	• • • • • • • • • • • • • • • • • • • •		•				
	d. Does the treatment works discharge	or transport treated or untreate	ed wastewater to ano	ther	Voc	./	No
	treatment works?				Yes	₩.	IVU

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 3 of 21

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

	party other than the applicant, provide:
Transporter name	
Mailing Address:	
Contact person:	
Title:	
Telephone numbe	T
Name:	
Name:	
Mailing Address:	
Contact person:	
,	
Title:	
Title: Telephone numbe	
Title: Telephone numbe If known, provide I Provide the average	ne NPDES permit number of the treatment works that receives this discharge.
Title: Telephone numbe If known, provide I Provide the average Does the treatmer A.8.a through A.8.	t works discharge or dispose of its wastewater in a manner not included in

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22. Page 4 of 21

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

### WASTEWATER DISCHARGES:

If you answered "yes" to question A.8.a, complete questions A.9 through A.12 once for each outfall (including bypass points) through which effluent is discharged. Do not include information on combined sewer overflows in this section. If you answered "no" to question A.8.a, go to Part B, "Additional Application Information for Applicants with a Design Flow Greater than or Equal to 0.1 mgd."

	escription of Outfall.		
a.	Outfall number	001	
b.	. Location	(City or town, if applicable)	22603 (Zip Code)
		Frederick County	<u>Virginia</u>
		(County) 39 deg 10' 36"	(State) 78 deg 04' 29"
		(Latitude)	(Longitude)
¢.	Distance from shore	e (if applicable)	N/A ft.
d.	Depth below surface	e (if applicable)	N/A_ ft.
e.	Average daily flow ra	ate	7.574 mgd
f.	Does this outfall hav periodic discharge?	ve either an intermittent or a	Yes No (go to A.9.g.)
	If yes, provide the fo	ollowing information:	
	Number of times per	r year discharge occurs:	
	Average duration of	each discharge:	
	Average flow per dis	scharge:	mgd
	Months in which disc	charge occurs:	
		vith a diffuser?	Yes No
g.	Is outfall equipped w		
	is outfall equipped w escription of Receiving		
	escription of Receivin	ng Waters.	
0. Da	escription of Receiving w	ng Waters. vater Opequon Creek	Dpequon, Waterbody VAV-B08R
0. Da	escription of Receiving watershed	ng Waters. vater Opequon Creek	
0. Da	escription of Receiving watershed United States Soil C	ng Waters. vater Opequon Creek (if known)	
a.	escription of Receiving watershed United States Soil C Name of State Mana	ng Waters.  vater Opequon Creek  (if known) C	shed code (if known): Not Known  Potomac
a. b.	Name of receiving watershed United States Soil C Name of State Mana United States Geolo	ng Waters.  vater Opequon Creek  (if known) C  conservation Service 14-digit waters agement/River Basin (if known):  regical Survey 8-digit hydrologic catal	shed code (if known): Not Known  Potomac

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22. Page 5 of 21

pequon Wa	atel Recial	HABOTEA	O v									
A.11. Descrip	iption of Tre	eatment.										
a. Wh	hat levels of	treatment a	are provid	ded? Ch	neck all t	hat a	pply.					
	✓ Pr	imary		******	<u>√</u> ;	Secon	ndary					
******	<b>√</b> Ac	lvanced			<u> </u>	Other.	. Describe:	Enhanced	Nutrient Re	moval for N	l and l	P
b. Indi	dicate the fo	llowing rem	oval rate	s (as ap	plicable	):						
Des	esign BOD <sub>5</sub> ı	removal <u>or</u> l	Design C	BOD <sub>s</sub> r	emoval			97		9	%	
Des	esign SS ren	noval						88		9	<b>%</b>	
Des	esign P remo	oval						<u>95</u>		9	%	
Des	esign N remo	oval						<u>92</u>		9	<b>%</b>	
Oth	her									9	%	
c. Wh	hat type of d	isinfection i	is used fo	- or the ef	ffluent fro	om thi	is outfall? If dis	infection varie	s by season,	please descr	ibe.	
							pochlorite. De					9
							or this outfall?			es ·		No
	es the treat						<i>or</i> 11.00 dation.			'es		No
									•			
.12. Effluen parame <u>dischar</u> collecte of 40 C At a mi	nt Testing I eters. Provi grged. Do n ted through CFR Part 13 inimum, eff	nformation ide the ind not include nanalysis ( 6 and othe fluent testi	n. All Ap icated el informa conducte er approp	plicant ffluent tion on ed usin	s that d testing combit g 40 CF	requi ned s R Pai equire	red by the per ewer overflow rt 136 methods ements for sta	mitting authors in this sect s. In addition andard metho	ority <u>for each</u> ion. All infor i, this data m ids for analyi	outfall thro mation repo ust comply es not addre	ugh wi rted m with Q essed	hich effluent is nust be based on tA/QC requireme by 40 CFR Part 1
o.12. Effluen parame dischar collecte of 40 C At a mi	nt Testing Interesting Interes	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Ap icated el informa conducte er approp	plicant ffluent tion on ed usin criate C must b	s that d testing combin g 40 CF gA/QC re e based	requined s R Par equire on a	red by the per ewer overflow rt 136 methods ements for sta	mitting authors in this sect s. In addition andard metho	ority <u>for each</u> ion. All infor I, this data m ds for analyi nust be no m	outfall thro mation repo ust comply es not addre	ugh wi rted m with Q essed ur and	hich effluent is nust be based on tA/QC requireme by 40 CFR Part 1 one-half years a
.12. Effluen parame dischar collecte of 40 C At a mi	nt Testing II eters. Prov arged. Do n ted through CFR Part 13 inimum, eff	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Ap icated el informa conducte er approp	plicant ffluent tion on ed usin oriate C must b	s that d testing combin g 40 CF gA/QC re e based	requined s R Par equire on a	red by the per ewer overflow rt 136 method: ements for sta t least three s	mitting authors in this sect s. In addition andard metho	ority <u>for each</u> ion. All infor i, this data m ds for analyt nust be no m	outfall thro mation repo ust comply es not addre lore than fou	ugh wi rted m with Q essed ir and	ust be based on A/QC requireme by 40 CFR Part 1 one-half years a
.12. Effluen parame dischar collecte of 40 C At a mi	nt Testing in eters. Proverged. Do noted through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Apicated et informa conducte or approping data	plicant ffluent tion on ed usin oriate C must b	s that d testing i combin g 40 CF QA/QC re e based	requined s R Par equire on a	red by the per ewer overflow rt 136 method: ements for sta t least three s: - LY VALUE	mitting authors in this sects. In addition and metho amples and m	ority <u>for each</u> ion. All infor i, this data m ds for analyt nust be no m	outfall thro mation repo ust comply es not addre lore than fou	ugh wi rted m with Q essed ir and	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a
.12. Effluen parame dischar collecte of 40 C At a mi  Outfall r	nt Testing in teters. Proverged. Do noted through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Ap licated et informa conducte er approp ng data	plicant ffluent of tion on ed usin priate C must b	s that d testing i combin g 40 CF QA/QC re e based	requined s R Par equire on a	red by the per ewer overflow rt 136 method: ements for state teast three so LY VALUE  Units  s.u.	mitting authors in this sects. In addition and metho amples and m	ority <u>for each</u> ion. All infor i, this data m ds for analyt nust be no m	outfall thro mation repo ust comply es not addre lore than fou	ugh wi rted m with Q essed ir and	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a
.12. Effluen parame dischar collecte of 40 C At a mi Outfall r	nt Testing in teters. Proverged. Do noted through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Apicated et informa conducte ir approping data	plicant ffluent tion on ed usin briate C must b	s that d testing i combin g 40 CF QA/QC re e based	required some services of the	red by the per ewer overflow rt 136 method: ements for sta t least three s: - LY VALUE	mitting authors in this sects. In addition and metho amples and m	ority <u>for each</u> ion. All infor i, this data m ds for analyt nust be no m	outfall thro mation repo ust comply ses not addre core than for ERAGE DAIL Units	ugh wi rted m with Q essed ir and	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a
H (Maximum)	nt Testing in eters. Proverged. Do noted through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis ( 6 and othe lluent testi	n. All Ap licated et informa conducte er approp ng data	plicant ffluent tion on ed usin oriate C must b	s that d testing i combin g 40 CF QA/QC re e based	required some sequired on a	red by the per ewer overflow rt 136 method: ements for sta t least three so LY VALUE  Units  S.U. S.U.	mitting authors in this sects. In addition and methors are methors are methors are methors and methors are methors are methors.	ority for each ion. All infor I, this data m ds for analyt nust be no m  AVE	outfall thro mation repo ust comply ses not addre core than for ERAGE DAIL Units	y VAL	hich effluent is nust be based on tA/QC requireme by 40 CFR Part 1 one-half years a
A.12. Effluen parame dischar collecte of 40 C At a mi Outfall r  H (Minimum) H (Maximum Tow Rate Temperature	nt Testing in eters. Provented through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis (6 and othe fluent testi	n. All Apicated et informa conducte ir approp ng data	plicant ffluent stion on ed usin oriate Comust be M. W. 6.86. 8.83. 22.42. 20.8. 29.8.	s that d testing combit g 40 CF ANQC re e based	required services of the servi	red by the per ewer overflow rt 136 method: ements for sta t least three s.  LY VALUE  Units  s.u.  S.u.  GD  G C	mitting authors in this sects. In addition and methors and methors and methors and methors are sections.	ority for each ion. All infor a, this data m ds for analyt nust be no m  AVI	outfall thro mation repo ust comply les not addre lore than for ERAGE DAIL Units	y VALI	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl
A.12. Effluen parame dischar collecte of 40 C At a mil Outfall r  H (Minimum) H (Maximum flow Rate  emperature * For ph	nt Testing is eters. Proverged. Do noted through CFR Part 13 inimum, efficient part 14 inimum, efficient part 15 inimum, e	nformation ide the ind not include a analysis of and othe fluent testi  O01  TER	n. All Ap licated ef informa conducte ir approp ng data	plicant ffluent of tion on ed usin oriate Comust be with the first between the first	s that d testing combin g 40 CF A/QC re e based  AXIMUN alue	required services of the control of	red by the per ewer overflow rt 136 method: ements for statt least three scale Units  LY VALUE  Units  s.u.  s.u.  GD  g C  g C	witting authors in this sects. In addition and ard methors and methors and methors are sections. Value 6.778  14.08 21.25	ority for each ion. All infor a, this data m ds for analyt nust be no m  AVI  AVI  de de	outfall thro mation repo ust comply es not addre fore than for  ERAGE DAIL  Units  GD  g C  g C	y VAL	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl
12. Effluen parame dischar collecte of 40 C At a mil Outfall r  H (Minimum) H (Maximum low Rate emperature * For ph	nt Testing in eters. Provented through CFR Part 13 inimum, efficient PARAMET	nformation ide the ind not include a analysis of and othe fluent testi  O01  TER	n. All Apicated el informa conducte rapproping data	plicant ffluent of tion on ed usin oriate Comust be with the first between the first	s that d testing combit g 40 CF QA/QC re e based  AXIMUM alue	required services of the control of	red by the per ewer overflow rt 136 method: ements for statt least three scale Units  LY VALUE  Units  s.u.  s.u.  GD  g C  g C	witting authors in this sect in addition and methor amples and method amples and met	ority for each ion. All infor a, this data m ds for analyt nust be no m  AVI  AVI  de de	outfall thro mation repo ust comply ses not addre fore than for  ERAGE DAIL  Units  GD g C	YVAL  146 693 733	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a UE  Number of Sample
.12. Effluen parame dischar collecte of 40 C At a mi  Outfall r  H (Minimum) H (Maximum low Rate emperature * For ph	nt Testing is eters. Proverged. Do noted through CFR Part 13 inimum, efficient part 14 inimum, efficient part 15 inimum, e	nformation ide the ind not include a analysis of and othe fluent testi  O01  TER	n. All Apicated el informa conducte rapproping data	plicant ffluent in tion on ad usin oriate Comust be with the control of the contr	s that d testing combit g 40 CF QA/QC re e based  AXIMUM alue	required services of the control of	red by the per ewer overflow rt 136 method: ements for statt least three scale Units  LY VALUE  Units  s.u.  s.u.  GD  g C  g C	witting authors in this sects. In addition and ard methors and methors and methors are sections. Value 6.778  14.08 21.25	ority for each ion. All infor a, this data m ds for analyt nust be no m  AVI  AVI  de de	ential thro mation repo ust comply les not addre lore than for  ERAGE DAIL  Units  3D g C g C ANALYT METHO	YVAL	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl
H (Minimum) H (Maximum low Rate emperature * For ph	nt Testing is eters. Proverged. Do noted through CFR Part 13 inimum, efficiency of the control o	nformation ide the ind not include a analysis of and other fluent testing the months of the include a analysis of and other fluent testing the include a analysis of an include a analysis of a analys	n. All Apricated et informa conducter appropring data	plicant ffluent in tion on ad usin priate Comust be with the second seco	s that d testing i combit g 40 CF AVQC re e based  AXIMUN alue  mum da M DAILY ARGE	required services of the control of	red by the per ewer overflow rt 136 method: ements for sta t least three so LY VALUE  Units  s.u.  s.u.  GD  g C  ue  AVERAG	witting authors in this sect in this sect is. In additional index and in the sect is a sect in the sec	ority for each ion. All infor a, this data m ds for analyt nust be no m  AVI  AVI  de  de  CHARGE	ential thro mation repo ust comply les not addre lore than for  ERAGE DAIL  Units  3D g C g C ANALYT METHO	YVAL	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl
H (Minimum) H (Maximum low Rate emperature * For ph	nt Testing is eters. Provented through CFR Part 13 inimum, eff number:  PARAMET PARAMET (Winter)  (Winter)  (Summer)  H please report of the provented through the provented thr	nformation ide the ind not include a analysis of and other fluent testing the months of the include a analysis of and other fluent testing the include a analysis of an include a analysis of a analys	n. All Apricated et informa conducter appropring data	plicant ffluent in tion on ad usin priate Comust be with the second seco	s that d testing i combit g 40 CF NA/QC re e based  AXIMUN alue  mum da M DAILY ARGE	required services of the control of	red by the per ewer overflow rt 136 method: ements for sta t least three so LY VALUE  Units  s.u.  s.u.  GD  g C  ue  AVERAG	witting authors in this sect in this sect is. In additional index and in the sect is a sect in the sec	rity for each ion. All infor a, this data mods for analyt nust be no m  AVI  ie  Mo  de  de  CHARGE  Number of  Samples	ential thro mation repo ust comply les not addre lore than for  ERAGE DAIL  Units  3D g C g C ANALYT METHO	YVAL	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl
H (Minimum) H (Maximum low Rate emperature * For ph  ONVENTION OCHEMICAL	nt Testing is eters. Provented through CFR Part 13 inimum, efficient of the control of the contr	nformation ide the ind not include analysis (6 and othe fluent testing the include analysis (7 and othe fluent analysis). The idea of the include analysis (8 and othe fluent testing the include analysis) and include analysis (8 and other include analysis). The include analysis (8 and other include analysis) and include analysis (8 and other include analysis) analysis (8 analysis) analysis	n. All Apricated et informa conducte ar approping data mum and M//	plicant ffluent in tion on ad usin priate Comust be with the second seco	s that d testing is combined to the combined t	required services of the control of	red by the per ewer overflow rt 136 method: ements for sta t least three s.  LY VALUE  Units  S.U.  S.U.  GD  G C  ue  AVERAG	mitting authors in this sectors. In additional methors and methors and methors are sectors. Value 6.778 14.08 21.25 EDAILY DIS	AVI  AVI  AVI  AVI  CHARGE  Number o Samples	outfall thro mation repo ust comply es not addre fore than for  ERAGE DAIL Units  GD g C g C ANALYT METHO	YVAL	hich effluent is nust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl  61  3  2  ML / MDL
A.12. Effluen parame dischar collecte of 40 C At a mil Outfall r  H (Minimum) H (Maximum low Rate emperature * For ph	nt Testing is eters. Proverged. Do noted through CFR Part 13 inimum, efficiency of the content o	nformation ide the ind not include a analysis (6 and other fluent testing the individual of the indivi	n. All Applicated et informa conducte rapproping data and mum and M/	plicant ffluent in tion on ad usin priate Comust be with the second seco	s that d testing is combined to the combined t	required services of the control of	red by the per ewer overflow rt 136 method: ements for statt least three sizes.  LY VALUE  Units  s.u. s.u. GD eg C eg C ue  AVERAG  Conc.	mitting authors in this sects. In addition and are method amples and method amples are method amples and method amples a	rity for each ion. All infor a, this data mods for analyt nust be no m  AVI  ie  Mo  de  de  CHARGE  Number of  Samples	outfall thro mation repo ust comply les not addre lore than for  ERAGE DAIL  Units  3D g C g C ANALYT METHO f	YVAL	hich effluent is ust be based on AVQC requireme by 40 CFR Part 1 one-half years a  UE  Number of Sampl  61  3  2  ML / MDL

EPA Form 3

	5552					m Approved 1/14/99 fB Number 2040-0086
			<u> </u>			
are provided?	Check all that	apply.				
•	√ Oth	•	Enhanced	Nutrient R	emoval for N and	d P
- noval rates (a	s applicable):					
Design CBO	D <sub>s</sub> removal		<u>97</u>		%	
	v		88		%	
			95		%	
			92		%	
					%	
is used for th	e effluent from	this outfall? If disi	nfection varie	s by season,	please describe.	
						fite
nation, is decl	nlorination used	for this outfall?			Yes	No
have post ae	ration?			✓ .	Yes	No
		AILY VALUE		AV	ED 4 OF D 4 11 3 (1 )	ALUE
	Value	Units	Valu		Units Units	Number of Samples
6.8		Units s.u.	Valu			
6.8i 8.8i	3 3	s.u. s.u.		e	Units	Number of Samples
8.8 <sup>3</sup> 22.	3 42	s.u. s.u. MGD	6.778	e	Units GD 1	Number of Samples 461
8.8 22.4 20.8	3 42 I	s.u. s.u. MGD deg C	6.778 14.08	M de	Units  GD 1 eg C 6	Number of Samples  461
8.8 22. 20. 29.	3 42 I	s.u. s.u. MGD deg C deg C	6.778	M de	Units  GD 1  eg C 6	Number of Samples 461
22 20 29 mum and a m MAXII DIS	3 3 42   I 8 8 8 waximum daily v MUM DAILY CHARGE	s.u. s.u. MGD deg C deg C zalue AVERAG	6.778 14.08 21.25	M de de	GD 1 eg C 6 eg C 7  ANALYTICAL METHOD	Number of Samples  461 93
22 20 29 mum and a m	3 3 42 8 8 aximum daily v	s.u. s.u. MGD deg C deg C	6.778 14.08 21.25	M de	Units  GD 1  eg C 6  eg C 7  ANALYTICAL METHOD	Number of Samples  461  93
8.8: 22 20 29 mum and a m MAXII DIS Conc.	3 3 42   I 8 8 8 waximum daily v MUM DAILY CHARGE	s.u. s.u. MGD deg C deg C zalue AVERAG	6.778 14.08 21.25	M de de	Units  GD 1  eg C 6  eg C 7  ANALYTICAL METHOD	Number of Samples  461  93
8.8: 22 20 29 mum and a m MAXII DIS Conc.	3 42 48 48 49 49 49 49 49 49 49 49 49 49 49 49 49	s.u. s.u. MGD deg C deg C zalue AVERAG	6.778 14.08 21.25	M de de CHARGE Number of Samples	Units  GD 1  eg C 6  eg C 7  ANALYTICAL METHOD  5210B	Number of Samples  461 93 32 ML / MDL  5.0 mg/l
22 29 mum and a m MAXII DIS Conc ENTIONAL C 17.35 11.20	3 42 42 8 8 aximum daily v MUM DAILY CHARGE Units COMPOUNDS. mg/l mg/l	s.u. s.u. MGD deg C deg C value  AVERAG Conc.	6.778 14.08 21.25 E DAILY DIS Units  mg/l mg/l	M de de CHARGE Number a Samples 732 258	Units   GD   1   6   6   6   6   6   6   6   6   6	Number of Samples  461  93  32  ML / MDL
22 20 29 mum and a m MAXII DIS Conc.  ENTIONAL C	3 42 1 3 42 4 4 5 4 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	s.u. s.u. MGD deg C deg C value AVERAG 2.513	6.778 14.08 21.25 E DAILY DIS Units	M de de CHARGE Number of Samples	Units  GD 1  eg C 6  eg C 7  ANALYTICAL METHOD  5210B	Number of Samples  461 93 32 ML / MDL  5.0 mg/l
	is used for the day additionation, is declared effluent information conducted user appropriate	is used for the effluent from d by addition of sodium fration, is dechlorination used have post aeration?  1. All Applicants that disclicated effluent testing requirements on combined conducted using 40 CFR For appropriate QA/QC requing data must be based or	Design CBOD <sub>s</sub> removal  is used for the effluent from this outfall? If disid by addition of sodium hypochlorite. Denation, is dechlorination used for this outfall? have post aeration?  In All Applicants that discharge to waters licated effluent testing required by the perion information on combined sewer overflow conducted using 40 CFR Part 136 methods are appropriate QA/QC requirements for sta	Design CBOD <sub>5</sub> removal  97  88  95  92  is used for the effluent from this outfall? If disinfection varies of the use of this outfall? If disinfection varies of the use of this outfall? If disinfection varies of the use of this outfall? If disinfection varies of the use of this outfall?  have post aeration?  n. All Applicants that discharge to waters of the US mulicated effluent testing required by the permitting author information on combined sewer overflows in this section of the use of t	Design CBOD <sub>s</sub> removal  97  88  95  92  is used for the effluent from this outfall? If disinfection varies by season, and by addition of sodium hypochlorite. Dechlorination by addition thation, is dechlorination used for this outfall?  have post aeration?  All Applicants that discharge to waters of the US must provide elicated effluent testing required by the permitting authority for each information on combined sewer overflows in this section. All information on combined sewer overflows in this section. All information on combined sewer overflows in this section. All are appropriate QA/QC requirements for standard methods for analying data must be based on at least three samples and must be no respective.	Design CBOD <sub>s</sub> removal  97  88  95  92  %  is used for the effluent from this outfall? If disinfection varies by season, please describe.  d by addition of sodium hypochlorite. Dechlorination by addition of sodium bisultation, is dechlorination used for this outfall?  have post aeration?  All Applicants that discharge to waters of the US must provide effluent testing deflicated effluent testing required by the permitting authority for each outfall through information on combined sewer overflows in this section. All information reported conducted using 40 CFR Part 136 methods. In addition, this data must comply with an appropriate QA/QC requirements for standard methods for analytes not addresse ing data must be based on at least three samples and must be no more than four an


Opequon Water Reclamation Facility VA0065552


# BASIC APPLICATION INFORMATION


PAF	et B	. ADDITIONAL APPLICATION INFORMATION FOR APPLICANTS WITH A DESIGN FLOW GREATER THAN OR EQUAL TO 0.1 MGD (100,000 gallons per day).
All a	pplic	ants with a design flow rate ≥ 0.1 mgd must answer questions B.1 through B.6. All others go to Part C (Certification).
3.1.	Inf	low and Infiltration. Estimate the average number of gallons per day that flow into the treatment works from inflow and/or infiltration.
	Bri	efly explain any steps underway or planned to minimize inflow and infiltration.
	<u>Ci</u>	ty of Winchester and Frederick County Sanitation Authority have on going program for I/I reduction.
3.2.	Thi	pographic Map. Attach to this application a topographic map of the area extending at least one mile beyond facility property boundaries. s map must show the outline of the facility and the following information. (You may submit more than one map if one map does not show entire area.)
	a.	The area surrounding the treatment plant, including all unit processes.
	b.	The major pipes or other structures through which wastewater enters the treatment works and the pipes or other structures through which treated wastewater is discharged from the treatment plant. Include outfalls from bypass piping, if applicable.
	C.	Each well where wastewater from the treatment plant is injected underground.
	ď.	Wells, springs, other surface water bodies, and drinking water wells that are: 1) within 1/4 mile of the property boundaries of the treatment works, and 2) listed in public record or otherwise known to the applicant.
	e.	Any areas where the sewage sludge produced by the treatment works is stored, treated, or disposed.
	f.	If the treatment works receives waste that is classified as hazardous under the Resource Conservation and Recovery Act (RCRA) by truck, rail, or special pipe, show on the map where that hazardous waste enters the treatment works and where it is treated, stored, and/or disposed.
	back chlo	cess Flow Diagram or Schematic. Provide a diagram showing the processes of the treatment plant, including all bypass piping and all true power sources or redundancy in the system. Also provide a water balance showing all treatment units, including disinfection (e.g., rination and dechlorination). The water balance must show daily average flow rates at influent and discharge points and approximate daily rates between treatment units. Include a brief narrative description of the diagram.
3.4.	Ope	ration/Maintenance Performed by Contractor(s).
		any operational or maintenance aspects (related to wastewater treatment and effluent quality) of the treatment works the responsibility of a ractor?YesNo
	~	s, list the name, address, telephone number, and status of each contractor and describe the contractor's responsibilities (attach additional es if necessary).
	Nam	e: see attached list
	Maili	ng Address:
	Tele	phone Number:
	Door	
	r(05)	considiities of Contractor:
	uncc treat	eduled Improvements and Schedules of Implementation. Provide information on any uncompleted implementation schedule or impleted plans for improvements that will affect the wastewater treatment, effluent quality, or design capacity of the treatment works. If the ment works has several different implementation schedules or is planning several improvements, submit separate responses to question for each. (If none, go to question B.6.)
	a.	List the outfall number (assigned in question A.9) for each outfall that is covered by this implementation schedule.
		001
	b.	Indicate whether the planned improvements or implementation schedule are required by local, State, or Federal agencies.
		✓ YesNo


EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.


Form Approved 1/14/99 OMB Number 2040-0086
N FLOW GREATER THAN OR
rt C (Certification).
works from inflow and/or infiltration.
I reduction.
le beyond facility property boundaries. an one map if one map does not show
pipes or other structures through which
applicable.
he property boundaries of the treatment
ed.
ation and Recovery Act (RCRA) by ks and where it is treated, stored, and/or
ns and where it is treated, stored, and/or
nt, including all bypass piping and all nt units, including disinfection (e.g.
nt units, including disinfection (e.g, discharge points and approximate daily
e treatment works the responsibility of a
ctor's responsibilities (attach additional
eted implementation schedule or
n capacity of the treatment works. If the ubmit separate responses to question
ation schedule.
anon portogato.
te, or Federal agencies.
Page 7 of 2°

















Contractors performing maintenance or operational functions related to the Opequon Water Reclamation Facility (Item B.4. of Part B of Application)

Abel Pumps
79 N Industrial Park
Sewickley, PA 15143-2339
412-741-3222
Press feed pump parts repairs and service

Coastal Bioanalysts 6400 Enterprise Ct. Glouchester, VA 23061 804-694-8285 Toxic Monitoring

Environmental Systems Services 218 North Main Street Culpeper, VA 22701 540-825-6660 Contract Lab

Instrulogic
P0 Box 468
Round Hill, VA 20142-0468
540-338-2222
Flow meter calibration — press control system service

Miller & Anderson 4150 Martinsburg Pike Clearbrook, VA 22624 540-667-4757 Electrical, HVAC service

Substation Test Company
4110 Forrestville Rd.
Forrestville, MD 20747
301-967-3500
Main power switchgear, high voltage breaker, and transformer service

Universal Filtration 703 Bascomb Commercial Park Suite 103 Woodstock, GA 30189 770-592-7564 Filter press parts and service

chi ecconomica			
Note that will also do not			
very deletement to the second			
v diam v distinctive di mandi			
To the second discovery of the			
There is never to order to order to order			
and the second			
e mode e meno d'especialiste.			
And the second s			

#### FACILITY NAME AND PERMIT NUMBER: Form Approved 1/14/99 OMB Number 2040-0086 Opequon Water Reclamation Facility VA0065552 c If the answer to B.5.b is "Yes," briefly describe, including new maximum daily inflow rate (if applicable). The facility is undergoing expansion and treatment enhancements (CTO by December 2010) d. Provide dates imposed by any compliance schedule or any actual dates of completion for the implementation steps listed below, as applicable. For improvements planned independently of local, State, or Federal agencies, indicate planned or actual completion dates, as applicable. Indicate dates as accurately as possible. Schedule Actual Completion MM / DD / YYYY MM / DD / YYYY Implementation Stage - Begin construction \_\_\_\_/ \_\_\_/ \_\_\_\_ - End construction \_\_\_/\_\_/\_\_\_ \_\_\_/\_\_/\_\_\_ Begin discharge - Attain operational level \_\_\_/\_\_\_/\_\_\_\_ e. Have appropriate permits/clearances concerning other Federal/State requirements been obtained? Describe briefly: B.6. EFFLUENT TESTING DATA (GREATER THAN 0.1 MGD ONLY). Applicants that discharge to waters of the US must provide effluent testing data for the following parameters. Provide the indicated effluent testing required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analysis conducted using 40 CFR Part 136 methods. In addition, this data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. At a minimum, effluent testing data must be based on at least three pollutant scans and must be no more than four and one-half years old. Outfall Number: 001 MAXIMUM DAILY POLLUTANT AVERAGE DAILY DISCHARGE DISCHARGE Conc. Units Number of ANALYTICAL ML / MDL Conc. Samples METHOD CONVENTIONAL AND NONCONVENTIONAL COMPOUNDS. AMMONIA (as N) 8.45 mg/l 0.42 mg/l 839 1500NH3F 0.20 mg/l CHLORINE (TOTAL RESIDUAL, TRC) .11 mg/l 0.00 mg/l 1460 4500-CL-D 0.1 ma/l DISSOLVED OXYGEN 13.06 0.01 mg/l mg/l 9.21 mg/l 1460 4500-OG TOTAL KJELDAHL

9.61 mg/l 1.46 mg/l 236 4500Norg 0.5 mg/l NITROGEN (TKN) NITRATE PLUS NITRITE 6.42 3.03 241 4500NO3E mg/l mg/l 0.5 mg/l NITROGEN OIL and GREASE N/A N/A mg/l mg/l PHOSPHORUS (Total) .35 3.97 233 0.10 mg/l mg/l ma/l 4500PBE TOTAL DISSOLVED SOLIDS (TDS) N/A mg/l N/A mg/l OTHER

END OF PART B. REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM 2A YOU MUST COMPLETE

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 8 of 21

Opequon Water Reclamation Facility VA0065552


Form Approved 1/14/99 OMB Number 2040-0086

# DASIC ADDITION INFORMATION

BASIC APPLICATION INFORMATION								
PART C. CERTIFICATION								
applicants must complete all applicable sections	ection. Refer to instructions to determine who is an officer for the purposes of this certification. All of Form 2A, as explained in the Application Overview. Indicate below which parts of Form 2A you this certification statement, applicants confirm that they have reviewed Form 2A and have completed application is submitted.							
Indicate which parts of Form 2A you have co	mpleted and are submitting:							
Basic Application Information packet	Supplemental Application Information packet:							
	Part D (Expanded Effluent Testing Data)							
	Part E (Toxicity Testing: Biomonitoring Data)							
	Part F (Industrial User Discharges and RCRA/CERCLA Wastes)							
	Part G (Combined Sewer Systems)							
ALL APPLICANTS MUST COMPLETE THE FO	DLLOWING CERTIFICATION.							
designed to assure that qualified personnel prop who manage the system or those persons direct	and all attachments were prepared under my direction or supervision in accordance with a system erly gather and evaluate the information submitted. Based on my inquiry of the person or persons ly responsible for gathering the information, the information is, to the best of my knowledge and that there are significant penalties for submitting false information, including the possibility of fine							
Name and official title Jesse W. Moffett								
Signature	m / T							
Telephone number (540) 722-3579								
Date signed 8(T)								
Upon request of the permitting authority, you mu	ist submit any other information necessary to assess wastewater treatment practices at the treatment tents.							

SEND COMPLETED FORMS TO:

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.



# SECTION 2 SUPPLEMENTAL APPLICATION INFORMATION PART D, E AND F

# Frederick-Winchester Service Authority

Post Office Box 43 Winchester, Virginia 22604

Office: 107 North Kent Street County Office Complex Winchester, Virginia 22601 1-540-722-3579

August 12, 2010

Trevor Wallace Environmental Engineer Virginia Department of Environmental Quality Valley Regional Office 4411 Early Road P.O. Box 3000 Harrisonburg, VA 22801

Dear Mr. Wallace:

Reference: Waiver Requests for Reissuance of VPDES Permit No. VA0065552
Opequon Water Reclamation Facility

In proceeding with the complying of information and data for the reissuance permit request for the Opequon Water Reclamation Facility we are asking for the following waivers.

- Under section B.6 of Part B of the Form 2A application there are data requests made for the
  pollutants of oil and grease and total dissolved solid (TDS). We are requesting a waiver from
  reporting this information because of the lack of data for these pollutants. No analysis for
  these pollutants was conducted since the reissuance of the permit in 2001. From our review
  of past testing, analysis on the effluent has never been conducted for these pollutants.
- We are requesting a waiver from the requested scans called for in Part D Expanded Effluent Testing Data of the permit application. At the present time, the Opequon Water Reclamation Facility is nearing the completion of an expansion and upgrade which will greatly enhance the existing treatment process. It is anticipated that the facility will receive a Certificate to Operate (CTO) at its expanded capacity by the end of 2010. Under the existing permit with the issuance of that CTO we will be required to conduct a complete scan as called for in Part D within a year of the issuance and hence we believe a waiver is appropriate.

If there should be any additional information required for these waiver requests please feel free to contact me directly at 1-540-722-3579.

Sincerely,

Jesse W. Moffett Executive Director

Frederick-Winchester Service Authority



"Maintaining and Promoting the Values of the Community through Environmental Stewardship"

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

# SUPPLEMENTAL APPLICATION INFORMATION

#### PART D. EXPANDED EFFLUENT TESTING DATA

Refer to the directions on the cover page to determine whether this section applies to the treatment works.

Effluent Testing: 1.0 mgd and Pretreatment Treatment Works. If the treatment works has a design flow greater than or equal to 1.0 mgd or it has (or is required to have) a pretreatment program, or is otherwise required by the permitting authority to provide the data, then provide effluent testing data for the following pollutants. Provide the indicated effluent testing information and any other information required by the permitting authority for each outfall through which effluent is discharged. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analyses conducted using 40 CFR Part 136 methods. In addition, these data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136. Indicate in the blank rows provided below any data you may have on pollutants not specifically listed in this form. At a minimum, effluent testing data must be based on at least three pollutant scans and must be no more than four and one-half years old.

(Complete once for each outfall discharging effluent to waters of the United States.) Outfall number: AVERAGE DAILY DISCHARGE POLLUTANT MAXIMUM DAILY DISCHARGE ANALYTICAL ML/ MDL Conc. Units Mass Units Conc. Units Mass Units Number of METHOD Samples METALS (TOTAL RECOVERABLE), CYANIDE, PHENOLS, AND HARDNESS. ANTIMONY ARSENIC BERYLLIUM CADMIUM CHROMIUM COPPER LEAD MERCURY NICKEL SELENIUM SILVER THALLIUM ZINC CYANIDE TOTAL PHENOLIC COMPOUNDS HARDNESS (AS CaCO<sub>3</sub>) se this space (or a separate sheet) to provide information on other metals requested by the permit writer.

EPA Form 3510-2A (Rev. 1-99), Replaces EPA forms 7550-6 & 7550-22. Page 10 of 21



Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

Outfall number:	_ (Comp	lete ond	e for eac	ch outfall	discharg	ging efflu	ent to w	aters of	the United S	States.)	
POLLUTANT							DAILY	DISCHA		· · · · ·	
	Conc.		Mass	Units	Conc.	Units	Mass	Units	Number	ANALYTICAL	ML/ MDL
									of Samples	METHOD	
VOLATILE ORGANIC COMPOUNDS.					1		····				
ACROLEIN											
ACRYLONITRILE											
BENZENE					!						
BROMOFORM											
CARBON TETRACHLORIDE											
CLOROBENZENE											
CHLORODIBROMO-METHANE											
CHLOROETHANE											
2-CHLORO-ETHYLVINYL ETHER											
CHLOROFORM											
DICHLOROBROMO-METHANE									····		
1,1-DICHLOROETHANE											
1,2-DICHLOROETHANE											
TRANS-1,2-DICHLORO-ETHYLENE											
1,1-DICHLOROETHYLENE							423434670366774467377				
1,2-DICHLOROPROPANE											
1,3-DICHLORO-PROPYLENE									***************************************		
ETHYLBENZENE											
METHYL BROMIDE											
METHYL CHLORIDE		-									
METHYLENE CHLORIDE											
1,1,2,2-TETRACHLORO-ETHANE											
ETRACHLORO-ETHYLENE											
TOLUENE											

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 11 of 21



Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

Outfall number:									the United S	otates.)	
POLLUTANT	1	MAXIMUM DAILY DISCHARGE			A۱	AVERAGE DAILY DISCHARGE					
	Conc.		Mass	Units	Conc.	Units	Mass	Units	Number of Samples	ANALYTICAL METHOD	ML/ MDL
1,1,1-TRICHLOROETHANE											
1,1,2-TRICHLOROETHANE											
TRICHLORETHYLENE											
VINYL CHLORIDE											
Use this space (or a separate sheet	) to provide in	I formatio	n on other	volatile o	rganic co	mpounds	requeste	d by the p	permit writer.		
ACID-EXTRACTABLE COMPOUN	DS										
A SECOND CONTRACTOR OF THE CON						T				······································	·····
P-CHLORO-M-CRESOL							)				
2-CHLOROPHENOL											
2,4-DICHLOROPHENOL							***************************************				-
2.4-DIMETHYLPHENOL											
4,6-DINITRO-O-CRESOL											
2,4-DINITROPHENOL											
2-NITROPHENOL											
4-NITROPHENOL											
PENTACHLOROPHENOL											
PHENOL											
2,4,6-TRICHLOROPHENOL											
Use this space (or a separate sheet	to provide in	formatio	on other	acid-extra	octable co	mpounds	requeste	d by the	permit writer.		
BASE-NEUTRAL COMPOUNDS.		:									······································
DAGE-NEU FAAL COMPOUNDS.									T	<u> </u>	
ACENAPHTHENE											
ACENAPHTHYLENE											
ANTHRACENE											
BENZIDINE											
BENZO(A)ANTHRACÈNE											TO THE COLUMN TO
BENZO(A)PYRENE		***************************************									

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 12 of 21

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

(Complete once for each outfall discharging effluent to waters of the United States.) Outfall number: MAXIMUM DAILY AVERAGE DAILY DISCHARGE POLLUTANT DISCHARGE Conc. Units Mass Units Conc. Units Mass Units Number ANALYTICAL ML/ MDL METHOD of Samples 3,4 BENZO-FLUORANTHENE BENZO(GHI)PERYLENE BENZO(K)FLUORANTHENE BIS (2-CHLOROETHOXY) METHANE BIS (2-CHLOROETHYL)-ETHER BIS (2-CHLOROISO-PROPYL) ETHER BIS (2-ETHYLHEXYL) PHTHALATE 4-BROMOPHENYL PHENYL ETHER BUTYL BENZYL PHTHALATE 2-CHLORONAPHTHALENE 4-CHLORPHENYL PHENYL ETHER CHRYSENE DI-N-BUTYL PHTHALATE DI-N-OCTYL PHTHALATE DIBENZO(A,H) ANTHRACENE 1,2-DICHLOROBENZENE 1.3-DICHLOROBENZENE 1,4-DICHLOROBENZENE 3,3-DICHLOROBENZIDINE DIETHYL PHTHALATE DIMETHYL PHTHALATE 2,4-DINITROTOLUENE .,6-DINITROTOLUENE 1,2-DIPHENYLHYDRAZINE

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

Outfall number:									f the United S	States.)	
POLLUTANT	1		IM DAIL HARGE	AVERAGE DAILY DISCHARGE							
	Conc.		Mass	Units	Conc.	Units	Mass	Units	Number of Samples	ANALYTICAL METHOD	ML/ MDL
FLUORANTHENE											
FLUORENE	variantista de descripciones de construcción d										
HEXACHLOROBENZENE											
HEXACHLOROBUTADIENE											
HEXACHLOROCYCLO- PENTADIENE											
HEXACHLOROETHANE											
INDENO(1,2,3-CD)PYRENE											
ISOPHORONE											**************************************
NAPHTHALENE											
NITROBENZENE											
N-NITROSODI-N-PROPYLAMINE											
N-NITROSODI- METHYLAMINE											
N-NITROSODI-PHENYLAMINE											
PHENANTHRENE											
PYRENE											
1,2,4-TRICHLOROBENZENE					,						
Use this space (or a separate sheet) to	provide ir	formatio	n on other	base-neu	itral comp	ounds re	quested t	y the pe	rmit writer.		
Week (Mark 1997)											
Use this space (or a separate sheet) to	provide ir	formatio	n on other	pollutant	s (e.g., pe	sticides)	requested	i by the p	permit writer.		
AND THE RESERVE THE PROPERTY OF THE PROPERTY O											
					L		1				Ç

END OF PART D.
REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM
2A YOU MUST COMPLETE

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22. Page 14 of 21



Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

# SUPPLEMENTAL APPLICATION INFORMATION

## PART E. TOXICITY TESTING DATA

POTWs meeting one or more of the following criteria must provide the results of whole effluent toxicity tests for acute or chronic toxicity for each of the facility's discharge points: 1) POTWs with a design flow rate greater than or equal to 1.0 mgd; 2) POTWs with a pretreatment program (or those that are required to have one under 40 CFR Part 403); or 3) POTWs required by the permitting authority to submit data for these parameters.

- At a minimum, these results must include quarterly testing for a 12-month period within the past 1 year using multiple species (minimum of two species), or the results from four tests performed at least annually in the four and one-half years prior to the application, provided the results show no appreciable toxicity, and testing for acute and/or chronic toxicity, depending on the range of receiving water dilution. Do not include information on combined sewer overflows in this section. All information reported must be based on data collected through analysis conducted using 40 CFR Part 136 methods. In addition, this data must comply with QA/QC requirements of 40 CFR Part 136 and other appropriate QA/QC requirements for standard methods for analytes not addressed by 40 CFR Part 136.
- In addition, submit the results of any other whole effluent toxicity tests from the past four and one-half years. If a whole effluent toxicity test conducted during the past four and one-half years revealed toxicity, provide any information on the cause of the toxicity or any results of a toxicity reduction evaluation, if one was conducted.
- If you have already submitted any of the information requested in Part E, you need not submit it again. Rather, provide the information requested in question E.4 for previously submitted information. If EPA methods were not used, report the reasons for using alternate methods. If test summaries are available that contain all of the information requested below, they may be submitted in place of Part E.
   If no biomonitoring data is required, do not complete Part E. Refer to the Application Overview for directions on which other sections of the form to

complete.									
E.1. Required Tests.									
Indicate the number of whole effluent toxicity tests conducted in the past four and one-half years.  6 chronic 2 acute									
E.2. Individual Test Data. Complete the following chart for each whole effluent toxicity test conducted in the last four and one-half years. Allow one column per test (where each species constitutes a test). Copy this page if more than three tests are being reported.									
dotalist per test (whole east openie	Test number:		Test number:						
a. Test information.									
Test species & test method number									
Age at initiation of test			•••						
Outfall number	_	mary Reports attached a	ong with						
Dates sample collected	accompanying Report o	f Analysis for each test co	nducted						
Date test started									
Duration									
b. Give toxicity test methods followe	eđ.								
Manual title									
Edition number and year of publication									
Page number(s)									
c. Give the sample collection metho	d(s) used. For multiple grab sample	s, indicate the number of grab sample	s used.						
24-Hour composite									
Grab									
d. Indicate where the sample was to	aken in relation to disinfection. (Chec	k all that apply for each)							
Before disinfection									
After disinfection									
After dechlorination									

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 15 of 21

FACILITY NAME AND PERMIT NUMBER:	
Openuon Water Reclamation Facility VA0065552	

Form Approved 1/14/99 OMB Number 2040-0086

Opequon water recialitation racinty	VA000002		
	Test number:	Test number;	Test number:
e. Describe the point in the treatmer	nt process at which the sample was o	collected.	
Sample was collected:			
f. For each test, include whether the	test was intended to assess chronic	toxicity, acute toxicity, or both.	
Chronic toxicity			
Acute toxicity			
g. Provide the type of test performed	d.		
Static			
Static-renewal			
Flow-through			
h. Source of dilution water. If labora	atory water, specify type; if receiving	water, specify source.	
Laboratory water			
Receiving water			
i. Type of dilution water. It salt wate	r, specify "natural" or type of artificia	I sea salts or brine used.	
Fresh water			
Salt water			
j. Give the percentage effluent used	for all concentrations in the test seri	es.	
k. Parameters measured during the	test. (State whether parameter meet	ts test method specifications)	
pH			
Salinity			
Temperature			
Ammonia			
Dissolved oxygen			
I. Test Results.			
Acute:			
Percent survival in 100% effluent	%	%	%
LC <sub>50</sub>			
95% C.I.	%	%	%
Control percent survival	%	%	%
Other (describe)			

EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 16 of 21

FACILITY NAME AND PERMIT NUMBER: Deequon Water Reclamation Facility VAC	0065552		Form Approved 1/14/99 OMB Number 2040-0086
Chronic:			
NOEC	%	%	%
IC <sub>25</sub>	%	%	%
Control percent survival	%	%	%
Other (describe)	-		
m. Quality Control/Quality Assurance.			
Is reference toxicant data available?			
Was reference toxicant test within acceptable bounds?			
What date was reference toxicant test run (MM/DD/YYYY)?			
Other (describe)			
Yes ✓ No If yes, des	Test Information. If you have	submitted biomonitoring test informat	ion, or information regarding the ne permitting authority and a
REFER TO THE APPLICATION	END OF PA ON OVERVIEW TO D 2A YOU MUST (	ETERMINE WHICH OTH	ER PARTS OF FORM

FACILITY NAME AND PERMIT NUMBER: Opequon Water Reclamation Facility VA	0065552	Form Approved 1/14/ OMB Number 2040-	′99 0086
Chronic:			
NOEC	%	%	%
IC <sub>25</sub>	%	%	%
Control percent survival	%	%	%
Other (describe)	·		
m. Quality Control/Quality Assurance.	4		
Is reference toxicant data available?			
Was reference toxicant test within acceptable bounds?			
What date was reference toxicant test run (MM/DD/YYYY)?			
Other (describe)			
E.4. Summary of Submitted Biomonitoring cause of toxicity, within the past four all summary of the results.  Date submitted:  Summary of results: (see instructions)	g Test Information. If you have submitted biomornd one-half years, provide the dates the Information  (MM/DD/YYYY)  END OF PART E.  ON OVERVIEW TO DETERMINE 2A YOU MUST COMPLETE	toring test information, or information regard was submitted to the permitting authority an	
EPA Form 3510-2A (Rev. 1-99). Replaces EP	PA forms 7550-6 & 7550-22.	Pag	ge 17 of 21
	,		

FACILITY NAME: Opequon Water Reclamation Facility
PERMIT NUMBER: VA0065552

Toxicity Monitoring Summary Report Opequon Water Reclamation Facility

Test Species & test method number	C. dubia EPA 1002.0 & 2002.0 P. promelas EPA 1000.0 &2000.0	C. dubia EPA 1002.0 & 2002.0 P. promelas EPA 1000.0 &2000.0	C. dubia EPA 1002.0 & 2002.0 P. promelas EPA 1000.0 &2000.0	
test results submitted with DMR	Annual Report	Annual Report	Annual Report	
Outfall number	001	001	001	
Dates sample collected	1/30-2/2/06	6/27/07	1/14-1/17/08	
Date test started	1/31/06	6/28/07	1/15/08	
Duration	7 days	2 days	8 days	
b. Give the sample colle	ction method(s) used. For multiple gra	ab samples, indicate the number of gra	b samples used.	
24-Hour composite	3	1	1	
Grab				
c. Indicate where the sa	mple was taken in relation to disinfecti	on. (Check all that apply for each.		
Before disinfection				
After disinfection				
After dechlorination	✓	✓ .	✓	
d. Describe the point in	the treatment process at which the san	nple was collected.		
Sample was collected:	following contact basin	following contact basin	following contact basin	
e. For each test, include	whether the test was intended to asse	ess chronic toxicity, acute toxicity, or bo	oth	
Chronic toxicity	both		✓	
Acute toxicity	both	✓		
f. Give the percentage e	effluent used for all concentrations in the	ne test series.	***************************************	
Chronic Test	15.5, 31, 62, 81, 100 %		15.5, 31, 62, 81, 100 %	
Acute Test	6.3, 13, 25, 50, 100 %	6.3, 13, 25, 50, 100 %		
Acute:				
Percent survival in 100% effluent	100 %	100 %		
LC <sub>50</sub>	N/A %	N/A %		
95% C.I.	N/A %	N/A %		
Control percent survival	100 %	100 %	······································	
Other (describe)		1		
Chronic:				
NOEC	100, 100 %	%	100, 100 %	
IC <sub>25</sub>	N/A %	%	N/A, N/A %	
Control percent survival	100 %	%	100 98%	
Other (describe)	reporting % C. dubia, P. promelas	reporting % C. dubia, P. promelas	reporting % C. dubia, P. promelas	



FACILITY NAME: Opequon Water Reclamation Facility

PERMIT NUMBER: VA0065552

Test Species & test method number

Toxicity Monitoring Summary Report Opequon Water Reclamation Facility

C. dubia EPA 1002.0

C. dubía EPA 1002.0

Test Species & test method number  P. prometas EPA 1000		P. promelas EPA 1000.0	P. promelas EPA 1000.0		
test results submitted with DMR	Annual Report	4/10/10	7/10/10		
Dutfall number	001	001	001		
Dates sample collected	1/5/09	1/4 – 1/7/10	4/5-4/8/10		
Date test started	1/6/09	1/5/10	4/6/10		
Duration	7 days	6 days	5 days		
b. Give the sample collec		ab samples, indicate the number of gr	ab samples used.		
24-Hour composite	1	1	1		
Grab					
c. Indicate where the san	nple was taken in relation to disinfecti	ion. (Check all that apply for each.	1		
Before disinfection					
After disinfection					
After dechlorination	✓	<b>√</b>	<b>✓</b>		
d. Describe the point in the	ne treatment process at which the sar	mple was collected.			
Sample was collected:	following contact basin	following contact basin	following contact basin		
e. For each test, include whether the test was intended to assess chronic toxicity, acute toxicity, or both					
Chronic toxicity	✓	✓	. ✓		
Acute toxicity					
f. Give the percentage ef	fluent used for all concentrations in the	he test series.	A AMANGAMAN AND AND AND AND AND AND AND AND AND A		
Chronic Test	16, 32, 64, 82, 100%	16, 32, 64, 82 100 %	16, 32, 64, 82 100 %		
Acute Test					
Acute:					
Percent survival in 100% effluent					
LC <sub>50</sub>					
95% C.1.					
Control percent survival					
Other (describe)					
Chronic:					
NOEC	100 %	100, 100 %	100, 100 %		
1C <sub>25</sub>	N/A	N/A,N/A	N/A,N/A		
Control percent survival	88 %	90, 98 %	100 98 %		
Other (describe)	reporting % P. promelas	reporting % C. dubia, P. promelas	reporting % C. dubia, P. promelas		

FACILITY NAME: Opequon Water Reclamation Facility


Toxicity Monitoring Summary Report Opequon Water Reclamation Facility

PERMIT NUMBER: VA0065552

			**************************************
Test Species & test method number	C. dubia EPA 1002.0 P. promelas EPA 1000.0		
test results submitted with DMR	**************************************		
Outfall number	001		
Dates sample collected	7/6-7/10/10		
Date test started	7/7/10		
Duration	6 days		
b Give the sample coll	ection method(s) used. For multiple gr	ab samples, indicate the number of gra	ab samples used.
24-Hour composite	1		
Grab			
c. Indicate where the sa	ample was taken in relation to disinfect	on. (Check all that apply for each.	
Before disinfection			
After disinfection			
After dechlorination	✓	·	
d. Describe the point in	the treatment process at which the sar	nple was collected.	
Sample was collected:	following contact basin		
e. For each test, include	e whether the test was intended to asse	ess chronic toxicity, acute toxicity, or b	oth
Chronic toxicity	$\checkmark$		
Acute toxicity			
f. Give the percentage	effluent used for all concentrations in the	ne test series.	
Chronic Test	16, 32, 64, 82, 100 %		
Acute Test			
Acute:			
Percent survival in 100% effluent			
LC <sub>50</sub>			
95% C.I.			
Control percent survival			
Other (describe)			
Chronic:			
NOEC	100, 100 %	19 Pt (PAN)	
IC <sub>25</sub>	N/A,N/A %	Make a market of the second of	
Control percent survival	100, 100 %		
Other (describe)	reporting % C. dubia, P. promelas		



Client: City of Winchester
Project ID: WINC0601
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552
Sample Period: 1/30/06 to 2/2/06



# Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:	Prepared By:
Ms. Tara Taylor	Coastal Bioanalysts, Inc.
Public Utilities Department	6400 Enterprise Court
City of Winchester	Gloucester, VA 23061
P.O. Box 75	(804) 694-8285
Winchester, VA 22604	www.coastalbio.com
	Contact: Peter F. De Lisle, Technical Director

Acute Lesi Resints				2400436566
Species-Test Method	48-h LC50	95% C.L.	T.U. <sub>Ac</sub>	NOAEC
C. dubia EPA, 2002.0	>100	N/A	<1.00	100
P. promelas EPA 2000.0	>100	N/A.	<1.00	100

Species- Test Method	Endooint	NOEC	LOEC	47113.7	303.4033	787. P7	TORE	48-h	LC50	
- AND RESIDENCE	- Comment of the Comm	I.C.C.		ChrV	PMSD	T.U.c	IC25	LC50	95% C.L.	T.U.Ac
C. dubia	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1002,0	Reproduction	100	>100	>100	25	1.00	>100	N/A	N/A	N/A
P. promelas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	26	1.00	>100	N/A	N/A	N/A

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

Acute l'est Biological Sommes		······································	Sample 4	Concentra	tion (%)		
Species-Method	Endpoint	Control	6.3	13	25	50	100
C. dubia EPA, 2002.0	Survival (%):	100	100	100	100	100	100
P. promelas EPA 2000.0	Survival (%):	100	100	100	100	100	100

Chromic LestaBiological(Sim	mary/Data	Sample Concentration (%)						
Species-Method	Endpoint	Control	15.5	31	62	81	100	
C. dubia EPA 1002.0	Survival (%):	100	100	100	100	100	90	
	Repro (# young):	21,5	22.4	20.3	20.2	22.4	18.1	
P. promelas EPA 1000.0	Survival (%):	100	98	95	98	95	98	
	Biomass (mg):	0.757	0.575	0.633	0.699	0.584	0,598	

Test Information Species-Method	Start Date/Time End Date/Time	Organism Source	Hatch/Harvest Date/Time	Acclimation Temp.	Acclimation Water	Test Aerated?
C. dubia EPA 2002.0	2/1/06 1310 2/3/06 1315	CBI Stock	1/31/06 1625 2/1/06 0930	25° C	Mod. Hard Syn. FW	No
P. promelas EPA 2000.0	2/1/06 1315 2/3/06 1325	CBI Stock	1/29/06 1500 1/30/06 1600	25° C	Mod. Hard Syn. FW	No
C. dubia EPA 1002.0	1/31/06 1545 2/6/06 1450	CBI Stock	1/30/06 1620 1/30/06 2200	25° C	Mod Hard Syn FW	No
P. promelas EPA 1000.0	1/31/06 1600 2/7/06 1500	CBI Stock	1/30/06 1630 1/31/06 1100	25° C	Mod. Hard Syn. FW	No

Page 1 of 4 Report Pages
Total No. Printouts/Bench Sheets Attached: 16

Chent: City of Winchester
Project ID: WINC0601
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552
Sample Period: 1/30/06 to 2/2/06

alysts, Inc.

Sample Didution Water Data	Acuí	e Test		Coastal Blogna		
		Dilution	Sa	mple	Dilutio	n Water
Water Quality Parameter (Units)	Sample	Water	Mean	Std. Dev.	Mean	Std. Dev.
Arrival Temperature (°C)	2	N/A	2	0.6	N/A	N/A
Use Temperature (°C)	25	25	25	0.5	25	0
Conductivity (µS/cm)	1070	286	1124	207	288	6.9
pH (S.U.)	7.76	7.84	7.81	0.10	7.75	0.07
Dissolved Oxygen (mg/l)	8.2	8.2	8.2	0	8,2	0
Total Hardness (mg/l as CaCO3)	290	92	286	20	90	3.9
Alkalinity (mg/l as CaCO <sub>3</sub> )	219	63	220	6.6	63	1.3
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>N/A</td><td><q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<></td></q.l.<>	N/A	<q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<>	0	N/A	N/A
Ammonia (mo// NHN)	73	3.74	11	1 11	NI/A	NIA

1.1

1.1

N/A

Ammonia (mg/l NH3-N) N/A N/A Dilution water = Moderately hard synthetic freshwater made with ASTM Type I deionized water

2.3

CBI Sample I.D.	Collection Date/Time	Date(s)/Time(s) 1st Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC0601-A	1/30/06 1100	1/31/06 1545, 1600	N/A	Aerated 5 min
WINC0601-B	1/31/06 1100	2/1/06 1310, 1315 2/1/06 1430, 1440	2/2/06 1410, 1430	Aerated 3.5-5.5 min
WINC0601-C	2/2/06 1100	2/3/06 1440, 1540	2/4/06 1405, 1450 2/5/06 1500, 1600 2/6/06 1400	Aerated 4-5 min

acute tests

Test:	C. dubia 2002.0					P. promelas 2000.0						
% Conc:	Cont.	6.3	13	25	50	100	Cont.	6.3	13	25	50	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0.6	0.6	0.6	0.6	0.6	0.6	0	0	0	0	0	0
D.O.	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.1	8.0
(mg/l)	0.1	0.1	0.1	0.1	0.2	0.2	0.1	0,1	0.2	0.2	0.2	0.2
рĦ	7.65	7.65	7.67	7.70	7.74	7.82	7.71	7.67	7.68	7,74	7.84	7.95
(S.U.)	0.07	0.05	0.04	0.11	0.20	0.35	0.06	0.06	0.02	0.04	0.08	0.19

Chrome lest	Water Q	nalify(()	AeamSt	i#Dev.)				rm da	de const		A WEDI	146300
Test:	C. dubia 1002.0					P. promelas 1000.0						
% Conc:	Cont.	15.5	31	62	81	100	Cont.	15.5	31	62	81	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0.5	0.5	0.5	0.5	0.5	0.5	0.3	0.4	0.4	0.4	0.4	0.4
D.O.	8.1	8.1	8.0	8.0	7.9	7.9	8.1	8.1	8.0	7.9	7.9	7.9
(mg/l)	0.2	0.2	0.2	0.3	0.3	0.4	0.1	0.2	0.2	0.3	0.3	0.3
рH	7.57	7.65	7.67	7.73	7.78	7.95	7.47	7.50	7.56	7.71	7.81	7.91
(S.U.)	0.22	0.24	0.27	0.25	0.22	0.14	0.20	0.17	0.20	0.17	0.11	0.10
Cond.	293	413	528	775	916	1085	292	411	534	775	903	1086
(µS/cm)	5.6	12	18	45	64	73	6.2	16	22	55	75	86


Page 2 of 4 Report Pages
Total No. Printouts/Bench Sheets Attached: 16

Client: City of Winchester Project ID: WINC0601

Client Sample ID: Opequon WRF Outfall 001

Permit No: VA0065552

Sample Period: 1/30/06 to 2/2/06



Acute Lest QA/QC Species-Method (Ref. Test Date)	Reference To Data Source	iicant: KOliviin Animal Source	us: mg/l % Control Survival	48-h LC50	95% C.L./A.L. for LC50
C. dubia 2002.0	RTT	CBI	100	531	492-573
(1/25/06-1/27/06)	CC	CBI	100	562	509-614
P. promelas 2000.0	RTT	CBI	95	887	799-970
(1/10/06-1/13/06)	CC	CBI	100	897	801-993

Chronic liest QA/QC Reference Loxicant & C.J. Units. mg/L											
Species-Method	Data	Animal	Survi	Survival (%)		Reproduction (# Young)/Biomass (mg)					
(Ref. Test Date)	Source	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.		
C. dubia 1002.0	RTT	CBI	100	500	23.9	250	21	379	N/A		
(1/4/06-1/10/06)	CC	CBI	98	500	22,2	250	26	323	261-385		
P. promelas 1000.0	RTT	CBI	95	500	0.63	500	25	641	N/A		
(1/3/06-1/10/06)	CC	CBI	99	500	0.53	500	15	605	553-657		

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.

#### APPROVED:

Technical Director

#### GLOSSARY OF TERMS AND ABBREVIATIONS

A.L. (Acceptance Limits): The results of a given reference toxicant test are compared to the control chart mean value ± 2 standard deviations. These limits approximate the 95% probability limits for the "true" reference toxicant value.

Chronic Value (ChrV): The geometric mean of the NOEC and LOEC. Units are same as test concentration units.

C.L. (Confidence Limits): These are the probability limits, based on the data set and statistical model employed, that the "true value" lies within the limits specified. Typically limits are based on 95% or 99% probabilities.

Control chart: A cumulative summary chart of results from QC tests with reference toxicants. The results of a given reference toxicant test are compared to the control chart mean value and 95% Acceptance Limits (A.L.) (mean ± 2 standard deviations).

IC25: The concentration of sample or chemical, calculated from the data set using statistical models, causing a 25% reduction in test organism growth, reproduction, etc. The lower the IC25, the more toxic the chemical or sample. Units are same as test concentration units.

LC50: The concentration of sample or chemical, calculated from the data set using statistical models, causing a 50% reduction in test organism survival. The lower the LC50, the more toxic the chemical or sample. Units are same as test concentration units. Note: The LC50 value must always he associated with the duration of exposure. Thus 48-h LC50, 96-h LC50, etc. are calculated.

LOEC: Lowest-observable-effect-concentration. The lowest concentration of sample or chemical in a chronic test dilution series in which the test organisms exhibit a statistically significant reduction in any of the test end points (e.g. growth, survival, reproduction) compared to control organisms. Units are same as test concentration units.

PMSD; Percent Minimum Significant Difference: The minimum difference which can exist between a test treatment and the controls in a particular test and be statistically significant; a measure of test sensitivity. The lower the PMSD the more sensitive the test.

Page 3 of 4 Report Pages

Total No. Printouts/Bench Sheets Attached: 16

Citent: City of Winchester Project ID: WINC0602 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 6/27/06



## Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:	Prepared By:
Mr. Don Riggleman	Coastal Bioanalysts, Inc.
Public Utilities Department	6400 Enterprise Court
City of Winchester	Gloucester, VA 23061
P.O. Box 75	(804) 694-8285
Winchester, VA 22604	www.coastalbio.com
	Contact: Peter F. De Lisle, Technical Director

Acute Lest Results				
Species-Test Method	48-h LC50	95% C.L.	T.U. <sub>Ac</sub>	NOAEC
C. dubia EPA 2002.0	>100	N/A	<1.00	100
P. promelas EPA 2000.0	>100	N/A	<1.00	100

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

AcuteTest Biological Summa.	Sample Concentration (%)						
Species-Method	Endpoint	Control	6.3	13	25	50	100
C. đubia EPA 2002,0	Survival (%):	100	100	100	100	100	100
P. promelas EPA 2000.0	Survival (%):	100	100	100	100	100	100

Test Informations	Start Date/Time	Organism	Hatch/Harvest	Acclimation	Acclimation	Test
Species-Method	End Date/Time	Source	Date/Time	Temp.	Water	Aerated?
C. dubia	6/28/06 1630	CBI	6/27/06 1640		Mod. Hard	
EPA 2002.0	6/30/06 1620	Stock	6/28/06 0930	25° C	Syn. FW	No
P. promelas	6/28/06 1620	CBI	6/22/06 1100		Mod. Hard	
EPA 2000.0	6/30/06 1615	Stock	6/23/06 1030	25° C	Syn. FW	No

S Sample Dilution Water Datas &	Acut	e Test
		Dilution 7
Water Quality Parameter (Units)	Sample	Water
Arrival Temperature (°C)	1	N/A
Use Temperature (°C)	25	25
Conductivity (µS/cm)	953	296
pH (S.U.)	7.92	7.66
Dissolved Oxygen (mg/l)	8.2	8.2
Total Hardness (mg/l as CaCO <sub>3</sub> )	N.D.	84
Alkalinity (mg/l as CaCO <sub>3</sub> )	N.D.	59
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>N/A</td></q.l.<>	N/A
Ammonia (mg/l NH <sub>3</sub> -N)	<1.0	N/A

Dilution water = Moderately hard synthetic freshwater made with ASTM Type I deionized water

Sample Agmp Use Protectiment 5.242 8 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2										
	Collection	Date(s)/Time(s)	Date(s)/Time(s)							
CBI Sample LD.	Date/Time	1 <sup>st</sup> Used in Tests	Used in Renewals	Sample Adjustments						
WINC0602-B	6/27/06 1100	6/28/06 1620, 1630	N/A	Aerated 2 min						

Page 1 of 2 Report Pages Total No. Printouts/Bench Sheets Attached: 4

Client: City of Winchester Project ID: WINC0602 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 6/27/06

5	) }
	1
Coastal Bioanalyst	, Inc

Acute Icsi Wa	rter Qua	lity (Me	m/Stda-l	)eva)	do exerci			s de els				
Test:	and the state of t		C. dubid	2002.0				P	. promeli	zs 2000.C	1	
% Conc:	Cont	6.3	13	25	50	100	Cont.	6.3	13	25	50_	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0	0	0	0	0	0	0	0	0	0	0	0
D.O.	8.1	8.1	8.1	8.0	8.0	8.0	8.1	8.0	8.0	7.9	7.9	7.8
(mg/l)	0.1	0.1	0.1	0.2	0.2	0.2	0.1	0.2	0.3	0.3	0.4	0.5
pΗ	7.73	7.77	7.82	7.87	7.93	8.16	7.60	7.64	7.70	7.77	7.87	8.01
(S.U.)	0.09	0.09	0.10	0.12	0.17	0.24	0.09	80.0	0.06	0,05	0.03	0.10

'Arue Test QA/QC	Reference (o	vicant: kC/51/nii	s. mg/L 4 Test 0	rganismiSource: CBI	Stock:Cultures
Species-Method (Ref. Test Date)	Data Source	% Control Survival	48-h LC50	95% C.L./A.L. for LC50	RTT in Control?
C. dubia 2002.0	RTT	100	601	559-647	Yes
(6/27/06-6/29/06)	CC	100	568	515-622	
P. promelas 2000.0	RTT	100	917	735-1050	Yes
(6/27/06-6/29/06)	CC	99	891	788-994	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.

APPROVED:

Peter F. De Lisle, Ph.D. Technical Director 7/7/04 Date

#### GLOSSARY OF TERMS AND ABBREVIATIONS

A.L. (Acceptance Limits): The results of a given reference toxicant test are compared to the control chart mean value  $\pm$  2 standard deviations. These limits approximate the 95% probability limits for the "true" reference toxicant value.

C.L. (Confidence Limits): These are the probability limits, based on the data set and statistical model employed, that the "true value" lies within the limits specified. Typically limits are based on 95% or 99% probabilities.

Control chart: A cumulative summary chart of results from QC tests with reference toxicants. The results of a given reference toxicant test are compared to the control chart mean value and 95% Acceptance Limits (A.L.) (mean ± 2 standard deviations).

LC50: The concentration of sample or chemical, calculated from the data set using statistical models, causing a 50% reduction in test organism survival. The lower the LC50, the more toxic the chemical or sample. Units are same as test concentration units. Note: The LC50 value must always be associated with the duration of exposure. Thus 48-h LC50, 96-h LC50, etc. are calculated.

NA: Not applicable. N/D: Not determined or measured.

NOAEC: No-observable-acute-effect-concentration. The highest concentration of sample or chemical in an acute test dilution series in which the test organisms exhibit no statistically significant reduction in the test end point (e.g. survival) compared to control organisms. Units are same as test concentration units.

Q.L.: Quantitation Limit. Level, concentration, or quantity of a target variable (analyte) that can be reported at a specified degree of confidence.

T.U.: Toxic units. Expresses the relative toxicity of an effluent in such a manner that the larger the toxic unit value the more toxic the effluent, T.U. $_{AC} = 100/LCSO$ , T.U. $_{CR} = 100/NOEC$ . A dimensionless unit.

Page 2 of 2 Report Pages

Total No. Printouts/Bench Sheets Attached: 4

Client: City of Winchester
Project ID: WINC0801
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552
Sample Period: 1/14/08 to 1/17/08



# Report of Analysis: Whole Effluent Toxicity (WET)

ubmitted To:	Prepared By:
Ms. Jennifer Morgan	Coastal Bioanalysts, Inc.
Public Utilities Department	6400 Enterprise Court
City of Winchester	Gloucester, VA 23061
P.O. Box 75	(804) 694-8285
Winchester, VA 22604	www.coastalbio.com

lbio.com Contact: Peter F. De Lisle, Technical Director

Chronic Test I	lesuits 🐪			22:001		· · · · · ·	· * · · · · · · · · · · · · · · · · · ·		±- ₫ ,	
Species- Test Method	Endpoint	NOEC	LOEC	ChrY	PMSD	T.U.c	IC25	48-h LC50	LC50 95% C.L.	T.U.Ac
C. dubia	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1002.0	Reproduction	100	>100	>100	31	1.00	>100	N/A	N/A	N/A
P. prometas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	26	1.00	>100	N/A	N/A	N/A

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

Chronic Test Biological Sun	Sample Concentration (%)						
Species-Method	Endpoint	Control	16	32	64	82	100
C. dubia EPA 1002.0	Survival (%):	100	100	100	100	100	90
	Repro (# young):	24.7	25.3	29.0	26.1	29.2	25.0
P. promelas EPA 1000.0	Survival (%):	98	100	93	98	80	88
	Biomass (mg):	0.558	0.526	0.540	0.476	0.449	0.457

Test Information	_,	Organism	Hatch/Harvest	Acclimation	Acclimation	Test
Species-Method	End Date/Time	Source	Date/Time	Temp.	Water	Aerated?
C. dubia	1/15/08 1505	ÇBI	1/14/08 1630		Mod. Hard	
EPA 1002.0	1/22/08 1420	Stock	1/14/08 2200	25° C	Syn. FW	No
P. promelas	1/15/08 1425	CBI	1/14/08 1500		Mod. Hard	
EPA 1000.0	1/22/08 1430	Stock	1/15/08 1000	25° C	Syn. FW	No


Sample/Dilution Water Data	Chronic Test						
	Sar	nple	Dilutio	n Water			
Water Quality Parameter (Units)	Mean	Std. Dev.	Mean	Std. Dev.			
Arrival Temperature (°C)	1	0	N/A	N/A			
Use Temperature (°C)	25	0.8	25	0			
Conductivity (µS/cm)	1209	139	295	2.6			
pH (S.U.)	7.92	0.20	7.66	0.05			
Dissolved Oxygen (mg/l)	8.2	0.1	8.2	0			
Total Hardness (mg/l as CaCO <sub>3</sub> )	320	51	94	5.3			
Alkalinity (mg/I as CaCO <sub>3</sub> )	190	27	59	1.6			
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<>	0	N/A	N/A			
Ammonia (mg/l NH <sub>3</sub> -N)	<1.0	0	N/A	N/A			

Dilution water = Moderately hard synthetic freshwater made with ASTM Type I deionized water

Page 1 of 3 Report Pages
Total No. Printouts/Bench Sheets Attached: 16

Client: City of Winchester
Project ID: WINC0801
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552

Sample Period: 1/14/08 to 1/17/08



CBI Sample I.D.	Collection Date/Time	Date(s)/Time(s) 1st Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC0801-A	1/14/08 0715	1/15/08 1425, 1505	N/A	N/A
WINC0801-B	1/15/08 0715	1/16/08 1400, 1450	1/17/08 1400, 1455	N/A
WINC0801-C	1/17/08 0715	1/18/08 1400, 1505	1/19/08 1515, 1600 1/20/08 1430, 1520	Aerated 0-4.5 min
			1/21/08 1310, 1345	

Test:			C. dubid	1002.0				P	, promel	as 1000.	0	
% Conc:	Cont.	16	32	64	82	100	Cont.	16	32	64	82	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0.5	0.5	0.5	0.4	0.4	0.4	0.3	0.3	0.3	0.3	0.3	0.3
D.O.	8.1	8.1	8.1	8.0	8.0	8.0	8.1	8.1	8.0	7.9	7.8	7.7
(mg/l)	0.1	0.1	0.2	0.2	0.2	0.3	0.1	0,2	0.3	0.4	0.4	0.5
pН	7.57	7.74	7.86	8.03	8.11	8.16	7.54	7.62	7.73	7.84	7.92	7.97
(Ŝ.U.)	0.09	0.17	0.16	0.16	0.19	0.21	0.10	0.16	0.19	0.18	0.17	0.16
Cond.	294	443	596	889	1082	1221	303	442	595	855	1029	122
(µS/cm)	6.0	13	27	48	97	69	10	16	33	51	60	62

Chronic Test QA/QC	Refere	nce Tox	cant: KC	l Units:	mg/l T	est Organ	ism Sour	ee: CBI Stock	Cultures
Species-Method	Data	% St	% Survival Reproduction (# Young) or Biomass (mg)					ass (mg)	RTT in
(Ref. Test Date)	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.	Control?
C. dubia 1002.0	RTT	100	250	24.4	250	27	278	N/A	Yes
(1/4/08-1/11/08)	CC	96	500	21.9	250	24	342	253-431	
P. promelas 1000.0	RTT	100	500	0.71	500	14	593	N/A	Yes
(1/2/08-1/9/08)	CC	97	500	0.58	500	17	612	565-659	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.

APPROVED:

Peter F. De Lisle, Ph.D.

Technical Director

#### GLOSSARY OF TERMS AND ABBREVIATIONS

A.L. (Acceptance Limits): The results of a given reference toxicant test are compared to the control chart trean value  $\pm 2$  standard deviations. These timits approximate the 95% probability limits for the "true" reference toxicant value.

Chronic Value (ChrV): The geometric mean of the NOEC and LOEC. Units are same as test concentration units.

C.L. (Confidence Limits): These are the probability fimits, based on the data set and statistical model employed, that the "true value" lies within the limits specified. Typically limits are based on 95% or 99% probabilities.

Page 2 of 3 Report Pages Total No. Printouts/Bench Sheets Attached: 16

Client: City of Winchester Project ID: WINC0901 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 1/5/09 to 1/8/09



## Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:	Prepared By:
Ms. Jennifer Morgan	Coastal Bioanalysts, Inc.
Public Utilities Department	6400 Enterprise Court
City of Winchester	Gloucester, VA 23061
P.O. Box 75	(804) 694-8285
Winchester, VA 22604	www.coastalbio.com
,	Contact: Peter F. De Lisle, Technical Director

Chronic Test Results										
Species-								48-h	LC50	
Test Method	Endpoint	NOEC	LOEC	ChrV	PMSD	T.U.c	IC25	LC50	95% C.L.	T.U.Ac
P. promelas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	20	1.00	>100	N/A	N/A	N/A

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

Chronic Test Biological Sumn			Sample	Concentra	tion (%)		
Species-Method Endpoint		Control	16	32	64	82	100
P. promelas EPA 1000.0	Survival (%):	88	95	100	98	90	98
	Biomass (mg):		0.540	0.531	0.528	0.424	0.546


Test Information	Start Date/Time	Organism	Hatch/Harvest	Acclimation	Acclimation	Test
Species-Method	End Date/Time	Source	Date/Time	Temp.	Water	Aerated?
P. promelas	1/6/09 1205	CBI	1/5/09 1530		Mod, Hard	
EPA 1000.0	1/13/09 1215	Stock	1/6/09 1030	25° C	Syn. FW	No

Sample/Dilution Water Data		Chron	ic Test	
-	Sar	nple	Dilutio	n Water
Water Quality Parameter (Units)	Меап	Std. Dev.	Меап	Std. Dev.
Arrival Temperature (°C)	1	0.6	N/A	N/A
Use Temperature (°C)	25	0	25	0
Conductivity (µS/cm)	1020	48	294	3.1
pH (S.U.)	8.01	0.19	7.64	0.05
Dissolved Oxygen (mg/l)	8.2	0	8.2	0
Total Hardness (mg/l as CaCO <sub>3</sub> )	291	37	98	2.1
Alkalinity (mg/l as CaCO <sub>3</sub> )	196	30	59	0.5
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<>	0	N/A	N/A
Ammonia (mg/l NH <sub>3</sub> -N)	<1.0	0	N/A	N/A

Dilution water = Moderately hard synthetic freshwater made with ASTM Type I deionized water

Page 1 of 3 Report Pages Total No. Printouts/Bench Sheets Attached: 11

Client: City of Winchester Project ID: WINC0901 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 1/5/09 to 1/8/09



CBI Sample I.D.	Collection Date/Time	Date(s)/Time(s)  1 <sup>st</sup> Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC0901-A	1/5/09 0730	1/6/09 1205	N/A	Aerated 3.5 min
WINC0901-B	1/6/09 0730	1/7/09 1520	1/8/09 1105	Aerated 3-3.5 min
WINC0901-C	1/8/09 0730	1/9/09 1300	1/10/09 1130 1/11/09 1210 1/12/09 1150	Aerated 2.5-3 min

Test:	1	P. promelas 1000.0							
% Conc:	Cont.	16	32	64	82	100			
Temp.	25	25	25	25	25	25			
(°C)	0.3	0.3	0.3	0.3	0.3	0.3			
D.O.	7.5	7.5	7.5	7.5	7.5	7.4			
(mg/l)	0.7	0.7	0.8	0.7	0.7	8.0			
pН	7.40	7.57	7.72	7.94	8.02	8.07			
(S.U.)	0.25	0.26	0.25	0.16	0.13	0.11			
Cond.	298	406	519	740	867	1009			
(uS/cm)	4.4	12	16	26	34	35			

Chronic Test QA/QC	Refere	ence Tox	icant: KC	l Units:	mg/l T	est Organ	ism Sourc	e: CBI Stock	Cultures
Species-Method	Data	% Sı	% Survival Biomass (mg)						RTT in
(Ref. Test Date)	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.	Control?
P. promelas 1000.0	RTT	95	500	0.62	500	17	625	N/A	Yes
(1/6/09-1/13/09)	CC	99	500	0.65	500	16	615	579-651	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.

APPROVED:

Peter F. De Lisle, P Technical Director 19/09 Date

#### GLOSSARY OF TERMS AND ABBREVIATIONS


A.L. (Acceptance Limits): The results of a given reference toxicant test are compared to the control chart mean value  $\pm 2$  standard deviations. These limits approximate the 95% probability limits for the "true" reference toxicant value.

Chronic Value (ChrV): The geometric mean of the NOEC and LOEC. Units are same as test concentration units.

C.L. (Confidence Limits): These are the probability limits, based on the data set and statistical model employed, that the "true value" lies within the limits specified. Typically limits are based on 95% or 99% probabilities.

Page 2 of 3 Report Pages Total No. Printouts/Bench Sheets Attached: 11

Client: City of Winchester Project ID: WINC1001 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 1/4/10 to 1/7/10



## Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:
Ms. Jennifer Morgan
Public Utilities Department
City of Winchester
P.O. Box 75
Winchester, VA 22604

Prepared By: Coastal Bioanalysts, Inc. 6400 Enterprise Court Gloucester, VA 23061 (804) 694-8285

www.coastalbio.com Contact: Peter F. De Lisle, Technical Director

Chronic Test I	Chronic Test Results									-
Species-								48-h	LC50	
Test Method	Endpoint	NOEC	LOEC	ChrV	PMSD	T.U.C	IC25	LC50	95% C.L.	T.U.A.
Ĉ. dubia	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1002.0	Reproduction	100	>100	>100	27	1.00	>100	N/A	N/A	N/A
P. promelas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	13	1.00	>100	N/A	N/A	N/A

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

Chronic Test Biological Sum	mary Data	Sample Concentration (%)						
Species-Method	Endpoint	Control	16.0	32.0	64.0	82.0	100	
C. dubia EPA 1002.0	Survival (%):	90	90	100	100	90	100	
	Repro (# young):	28.1	29.5	31.9	28.0	27.4	29.2	
P. promelas EPA 1000.0	Survival (%):	98	98	98	100	100	100	
	Biomass (mg):	0.805	0.719	0.726	0.752	0.779	0.765	


Test Information Species-Method	Start Date/Time End Date/Time	Organism Source	Hatch/Harvest Date/Time	Acclimation Temp.	Acclimation Water	Test Aerated?
C. dubia	1/5/10 1420	CBI	1/4/10 1635		Mod. Hard	
EPA 1002.0	1/11/10 1555	Stock	1/4/10 2200	25° C	Syn. FW	No
P. prometas	1/5/10 1335	CBI	1/4/10 1600		Mod. Hard	
EPA 1000.0	1/12/10 1345	Stock	1/5/10 0830	25° C	Syn. FW	No

Sample/Dilution Water Data		Chron	ic Test	
	San	nple	Dilution	1 Water
Water Quality Parameter (Units)	Mean	Std. Dev.	Mean	Std. Dev.
Аrrival Temperature (°С)	1	0	N/A	N/A
Use Temperature (°C)	25	0	25	0.5
Conductivity (µS/cm)	1145	161	301	3.3
pH (S.U.)	8.17	0.26	7.99	0.06
Dissolved Oxygen (mg/l)	8.2	0	8.2	0
Total Hardness (mg/l as CaCO <sub>3</sub> )	276	86	100	0
Alkalinity (mg/l as CaCO <sub>3</sub> )	202	13	57	0
Total Residual Chlorine (mg/l)	<q.l,< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l,<>	0	N/A	N/A
Ammonia (mg/l NH3-N)	<1.0	0	N/A	N/A

<sup>\*</sup>Dilution water = Moderately hard synthetic freshwater

Page 1 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

Client: City of Winchester
Project ID: WINC1001
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552
Sample Period: 1/4/10 to 1/7/10



CBI Sample I.D.	Collection Date/Fime	Date(s)/Time(s)  1 <sup>st</sup> Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC1001-A	1/4/10 0730	1/5/10 1335, 1420	N/A	Aerated 1 min
WINC1001-B	1/5/10 0730	1/6/10 1445, 1545	1/7/10 1500, 1500	Aerated 0,5 min
WINC1001-C	1/7/10 0730	1/8/10 1310, 1330	1/9/10 1255, 1500 1/10/10 1140, 1345 1/11/10 1300	Aerated 0.5-1 min

Test:	. F		C. dubie	a 1002.0			P. promelas 1000.0					
% Cone:	Cont.	16.0	32.0	64.0	82.0	100	Cont.	16.0	32.0	64.0	82.0	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
D.O.	7.9	7.9	7.9	7.9	7.9	7.9	7.4	7.4	7.4	7.4	7.4	7.4
(mg/l)	0.4	0.4	0.4	0.4	0.4	0.4	0.8	0.4	0.4	0.4	0.4	0.4
pН	7.90	8.07	8.17	8.28	8.33	8.38	7.75	7.82	7.91	8.02	8.07	8.11
(S.U.)	0.07	0.11	0.15	0.19	0.21	0.23	0.26	0.31	0.28	0.23	0.22	0.23
Cond.	301	445	584	862	1028	1190	299	449	598	873	1044	1211
(uS/cm)	6.1	17	31	66	92	119	4.5	17	36	68	95	119

Chronic Test QA/QC	Refere	ence Tox	icant: KC	l Units:	mg/l T	est Organ	ism Sour	ce: CBI Stock	Cultures
Species-Method	Data	% St	ırvival	Rep	roduction	(# Young	) or Biom	ass (mg)	RTT in
(Ref. Test Date)	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.	Control?
C. dubia 1002.0	RTT	100	500	26.9	250	21	380	N/A	Yes
(1/3/10-1/10/10)	ÇC	97	500	22.9	250	29	303	215-390	
P. promelas 1000.0	RTT	98	500	0.72	500	20	591	N/A	Yes
(1/1/10-1/8/10)	CC	98	500	0.66	500	15	606	565-646	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.


APPROVED:

Peter F. De Lisle, Ph.D. Technical Director 1/18/10 Date

Page 2 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

Client: City of Winchester
Project ID: WINC1002
Client Sample ID: Opequon WRF Outfail 001
Permit No: VA0065552

Sample Period: 4/5/10 to 4/8/10



## Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:

Ms. Jennifer Morgan Public Utilities Department City of Winchester P.O. Box 75 Winchester, VA 22604

Prepared By: Coastal Bioanalysts, Inc. 6400 Enterprise Court Gloucester, VA 23061 (804) 694-8285 www.coastalbio.com

Contact: Peter F. De Lisle, Technical Director

Chronic Test I	Chronic Test Results									
Species- Test Method	Endpoint	NOEC	LOEC	ChrV	PMSD	T.U.c	IC25	48-h LC50	LC50 95% C.L.	T.U.,c
C. dubia	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1002.0	Reproduction	100	>100	>100	26	1.00	>100	N/A	N/A	N/A
P. promelas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	14	1.00	>100	N/A	N/A	N/A

Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicable.

Chronic Test Biological Sumi	nary Data	Sample Concentration (%)						
Species-Method	Endpoint	Control	16.0	32.0	64.0	82.0	100	
C. dubia EPA 1002.0	Survival (%):	100	100	100	100	100	90	
	Repro (# young):	22.9	23.8	25.2	24.5	23.9	22.4	
P. promelas EPA 1000.0	Survival (%):	98	98	95	98	95	93	
_	Biomass (mg):	0.703	0.685	0.639	0.638	0.627	0.641	


Test Information	Start Date/Time	Organism	Hatch/Harvest	Acclimation	· Acclimation	Test
Species-Method	End Date/Time	Source	Date/Time	Temp.	Water	Aerated?
C. dubia	4/6/10 1200	CBI	4/5/10 1215		Mod. Hard	
EPA 1002.0	4/11/10 1535	Stock	4/5/10 1400	25° C	Syn, FW	No
P. promelas	4/6/10 1240	CBI	4/5/10 1530		Mod. Hard	
EPA 1000.0	4/13/10 1250	Stock	4/6/10 0830	25° C	Syn. FW	No

Sample/Dilution Water Data	OTHER DESIGNATION OF THE PERSON OF THE PERSO	Chron	ic Test	
	San	nple	Dilution	i Water*
Water Quality Parameter (Units)	Mean	Std. Dev.	Mean	Std. Dev.
Arrival Temperature (°C)	1	0	N/A	N/A
Use Temperature (°C)	25	0.5	25	0
Conductivity (µS/cm)	1076	73	299	5.7
pH (S.U.)	8.11	0.06	7.89 '	0.05
Dissolved Oxygen (mg/l)	8.2	0.1	8.2	0
Total Hardness (mg/l as CaCO <sub>3</sub> )	325	6.1	93	3.0
Alkalinity (mg/l as CaCO <sub>3</sub> )	221	5.5	57	0
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<>	0	N/A	N/A
Ammonia (mg/l NH <sub>3</sub> -N)	<1.0	0	N/A	N/A

<sup>\*</sup>Dilution water = Moderately hard synthetic freshwater

Page 1 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

Client: City of Winchester
Project ID: WINC1002
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552
Sample Period: 4/5/10 to 4/8/10



Sample Aging/Use	/Pretreatment		COLOR A PROPERTY AND A STATE OF THE PROPERTY AND A STATE O	
CBI Sample I.D.	Collection Date/Time	Date(s)/Time(s)  1 <sup>st</sup> Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC1002-A	4/5/10 0730	4/6/10 1200, 1240	N/A	Aerated 1.5 min
WINC1002-B	4/6/10 0730	4/7/10 1215, 1305	4/8/10 1345, 1425	Aerated 1.5-2.5 min
WINC1002-C	4/8/10 0730	4/9/10 1325, 1405	4/10/10 1235, 1255 4/11/10 1435 4/12/10 1310	Aerated 2-2.5 min

Chronic Test	Water Q	uality (l	Mean/St	d. Dev.)								
Test;	different of the second		C. dubie	1002.0				P	promel	as 1000.	)	
% Conc:	Cont.	16.0	32.0	64.0	82.0	100	Cont.	16.0	32.0	64.0	82.0	100
Temp.	25	25	25	25	25	25	25	25	25	25	25	25
(°C)	0.5	0.5	0.5	0.5	0.5	0.5	0.4	0.4	0.4	0.4	0.4	0.4
D.O.	7.9	7.9	7.9	7.9	7.9	7.9	7.7	7.7	7.7	7.7	7.6	7.6
(mg/l)	0.3	0.3	0.3	0.3	0.3	0.3	0.6	0.6	0.6	0,6	0.6	0.6
pН	7.86	8.02	8.11	8.21	8.27	8.28	7.61	7.78	7.94	8.06	8.10	8.14
(S.U.)	0.07	0.07	0.05	0.07	0.11	0.12	0.24	0.24	0.19	0.11	0.07	0.06
Cond.	296	453	563	805	965	1106	300	433	579	825	977	1132
(µS/cm)	4.8	48	12	23	52	58	1.9	9.1	24	33	37	49

Chronic Test QA/QC	: Refere	ence Tox	icant: KC	l Units:	mg/l T	est Organ	ism Sour	ce: CBI Stock	Cultures
Species-Method	Data	% Sr	% Survival Reproduction (# Young) or Biomass (mg)				RTT in		
(Ref. Test Date)	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.	Control?
C. dubia 1002.0	RTT	80	500	17.4	250	20	388	N/A	Yes
- (4/1/10-4/7/10)	CC	97	500	22.8	250	29	303	214-392	
P. promelas 1000.0	RTT	95	500	0.80	500	14	634	N/A	Yes
(4/1/10-4/8/10)	CC	98	500	0.67	500	15	606	565-647	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory.

APPROVED:

Peter F. De Lisle, Ph.D. Technical Director 4/19/10 Date

Page 2 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

Client: City of Winchester Project ID: WINC1003 Client Sample ID: Opequon WRF Outfall 001 Permit No: VA0065552 Sample Period: 7/6/10 to 7/10/10



## Report of Analysis: Whole Effluent Toxicity (WET)

Submitted To:	
Ms. Jennifer Morgan	
Public Utilities Departn	ient
City of Winchester	
P.O. Box 75	

Winchester, VA 22604

Prepared By:
Coastal Bioanalysts, Inc.
6400 Enterprise Court
Gloucester, VA 23061
(804) 694-8285
www.coastalbio.com
Contact: Peter F. De Lisle, Technical Director

Chronic Test I	≷esults <sup>*</sup>									
Species-								48-h	LC50	
Test Method	Endpoint	NOEC	LOEC	ChrV	PMSD	T.U.c	IC25	LC50	95% C.L.	T.U.A.
C. dubia	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1002.0	Reproduction	100	>100	>100	42	1.00	>100	N/A	N/A	N/A
P, promelas	Survival	100	>100	>100	N/A	1.00	N/A	>100	N/A	<1.00
EPA 1000.0	Biomass	100	>100	>100	13	1.00	>100	N/A	N/A	N/A

\*Note: Details regarding test conduct and data analysis provided in attached bench sheets and printouts as applicab

Chronic Test Biological Sum	7		Sample	Concentra	tion (%)		
Species-Method	Endpoint	Control	16.0	32.0	64.0	82.0	100
C. dubia EPA 1002.0	Survival (%):	100	90	90	100	80	100
·	Repro (# young):	18.7	18.3	17.6	26.1	15.5	16.5
P. promelas EPA 1000.0	Survival (%):	100	100	100	98	100	100
_	Biomass (mg):	0.650	0.711	0.681	0.690	0.689	0.633

Test Information	Start Date/Time	Organism	Hatch/Harvest	Acclimation	Acclimation	Test
Species-Method	End Date/Time	Source	Date/Time	Temp.	Water	Aerated?
C. dubia	7/7/10 1345	CBI	7/6/10 2200		Mod. Hard	
EPA 1002.0	7/13/10 1625	Stock	7/7/10 0600	25° C	Syn, FW	No
P. promelas	7/7/10 1215	CBI	7/6/10 1600		Mod. Hard	
EPA 1000.0	7/14/10 1245	Stock	7/7/10 0900	25° C	Syn. FW	No

Sample/Dilution Water Data	Chronic Test					
	Şan	Sample		n Water*		
Water Quality Parameter (Units)	Mean	Std. Dev.	Меап	Std. Dev.		
Arrival Temperature (°C)	1	0.6	N/A	N/A		
Use Temperature (°C)	26	0.5	25	0		
Conductivity (µS/cm)	1354	53	300	3.2		
pH (S.U.)	8.17	0.07	7.90	0.07		
Dissolved Oxygen (mg/l)	8.2	0.1	8.2	-0		
Total Hardness (mg/l as CaCO <sub>3</sub> )	390	47	87	5.4		
Alkalinity (mg/l as CaCO <sub>3</sub> )	242	4.6	60	0,4		
Total Residual Chlorine (mg/l)	<q.l.< td=""><td>0</td><td>N/A</td><td>N/A</td></q.l.<>	0	N/A	N/A		
Ammonia (mg/l NH3-N)	<1.0	0	N/A	N/A		

\*Dilution water = Moderately hard synthetic freshwater




Page 1 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

_		
B		
ysts, ma		
000 A 000 A ole.		
5 3		
d?		

Client: City of Winchester

Project ID: WINC1003
Client Sample ID: Opequon WRF Outfall 001
Permit No: VA0065552

Sample Period: 7/6/10 to 7/10/10



CBI Sample I.D.	Collection Date/Time	Date(s)/Time(s) 1st Used in Tests	Date(s)/Time(s) Used in Renewals	Sample Adjustments
WINC1003-A	7/6/10 0730	7/7/10 1215, 1345	N/A	Aerated I min
WINC1003-B	7/7/10 0730	7/8/10 1415, 1520	7/9/10 1440, 1545	Aerated 1 min
WINC1003-C	7/10/10 0730	7/10/10 1415, 1445	7/11/10 1400, 1455 7/12/10 1300, 1510 7/13/10 1310	Aerated 2-3 min

Test:			C. dubie	a 1002.0				P	. promel	as 1000.	0	
% Conc:	Cont.	16.0	32.0	64.0	82.0	100	Cont.	16.0	32.0	64.0	82.0	100
Temp.	26	26	26	26	26	26	25	25	25	25	25	25
(°C)	0.5	0.5	0.5	0.5	0.5	0.5	0.4	0.4	0.4	0.4	0.4	0.4
D.O.	7.8	7.8	7,8	7.9	7.9	7.9	7.6	7.5	7.5	7.6	7.6	7.5
(mg/l)	0.4	0.4	0.4	0.3	0.3	0.4	0.7	8.0	0.8	0.6	0.7	0.7
pН	7.85	8.02	8.14	8.27	8.30	8.32	7.70	7.80	7.92	8.07	8.16	8,20
(Ŝ.U.)	0.10	0.10	0.08	0.10	0.12	0.13	0.22	0.27	0.23	0.19	0.10	0.08
Cond.	303	452	626	937	1127	1307	302	464	628	940	1116	1326
(uS/cm)	2.2	9.2	8.2	22	19	6.6	1.9	7.7	14	27	27	11

Chronic Test QA/QC Reference Toxicant: KCl Units: mg/l Test Organism Source: CBI Stock						Cultures			
Species-Method	Data	% St	ırvival	Rep	roduction	(#Young	) or Biom	ass (mg)	RTT in
(Ref. Test Date)	Source	Cont.	NOEC	Cont.	NOEC	PMSD	IC25	IC25 A.L.	Control?
C. dubia 1002.0	RTT	100	500	28.8	125	22	295	N/A	Yes
(7/1/10-7/7/10)	CC	97	500	23.1	250	27	306	214-399	
P. promelas 1000.0	RTT	98	500	0.65	500	14	614	N/A	Yes
(7/1/10-7/8/10)	CC	98	500	0.68	500	15	606	563-648	

Note: RTT = Reference Toxicant Test, CC = Control Chart, Cont. = Control group.

The results of analysis contained within this report relate only to the sample as received in the laboratory. This report shall not be reproduced except in full without written approval from the laboratory. Unless noted below, these test results meet all requirements of NELAP.

APPROVED:

Peter F. De Lisle, Ph.D. Technical Director

7/16/10 Date

Deviations from, additions to, or exclusions from the test method, non-standard conditions or data qualifiers and, as appropriate, a statement of compliance/non-compliance: NONE



Page 2 of 3 Report Pages
Total No. Printouts/Bench Sheets/Documents Attached: 17

agent and an agent and agent a			
ma de de la constanta de la co			
A di			
and under the control of the control			
Excellent control of the Control of			
openion and distributions of the second of t			
Managar Constitutive et al. 4 cons			
Solder majoritude (a monta)			
A Light Library ( Types up - 1)			

#### FACILITY NAME AND PERMIT NUMBER:

Opequon Water Reclamation Facility VA0065552

Form Approved 1/14/99 OMB Number 2040-0086

## SUPPLEMENTAL APPLICATION INFORMATION

PAI	RT F. INDUSTRIAL USER DISCHARGES AND RCRA/CERCLA WASTES
	reatment works receiving discharges from significant industrial users or which receive RCRA, CERCLA, or other remedial wastes must plete Part F.
GEI	NERAL INFORMATION:
F.1.	Pretreatment Program. Does the treatment works have, or is it subject to, an approved pretreatment program?
	✓ YesNo
F.2.	Number of Significant Industrial Users (SIUs) and Categorical Industrial Users (CIUs). Provide the number of each of the following types of industrial users that discharge to the treatment works.
	a. Number of non-categorical SIUs. 6
	b. Number of ClUs. 0
SIG	NIFICANT INDUSTRIAL USER INFORMATION:
Supp	bly the following information for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 provide the information requested for each SIU.
F.3.	Significant Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit additional pages as necessary.
	Name: Significant User Information provided on separate attachment for each user
	Mailing Address:
F.4.	Industrial Processes. Describe all of the industrial processes that affect or contribute to the SIU's discharge.
F.5.	discharge.
	Principal product(s):
	Raw material(s):
F.6.	Flow Rate.
	Process wastewater flow rate. Indicate the average daily volume of process wastewater discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent.  gpd (continuous orintermittent)
	gpu
	<ul> <li>Non-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent.</li> </ul>
	gpd (continuous orintermittent)
F.7.	Pretreatment Standards. Indicate whether the SIU is subject to the following:
	a. Local limits
	b. Categorical pretreatment standardsYes
	If subject to categorical pretreatment standards, which category and subcategory?


EPA Form 3510-2A (Rev. 1-99). Replaces EPA forms 7550-6 & 7550-22.

Page 18 of 21

}	LITY NAME AND PERMI uon Water Reclamatio		5552	Form Approved 1/14/99 OMB Number 2040-0086
F.8.	Problems at the Treatm			IU. Has the SIU caused or contributed to any problems (e.g.,
V-10-10-10-10-10-10-10-10-10-10-10-10-10-	YesNo	If yes, describ	e each episode.	
			BY TRUCK, RAIL, OR DEDICAT	
F.9.	RCRA Waste. Does the pipe?Yes _✓_N	treatment works re to (go to F.12.)	ceive or has it in the past three year	s received RCRA hazardous waste by truck, rail, or dedicated
F.10.	Waste Transport. Meth	nod by which RCRA	waste is received (check all that ap	p(y):
	Truck	Rail	Dedicated Pipe	
F.11.	Waste Description. Given	ve EPA hazardous	waste number and amount (volume	or mass, specify units).
	EPA Hazardous Waste N	<u>Number</u>	<u>Amount</u>	<u>Units</u>
				water and the second se
			BALLANDA CHARLES AND	
CER	CLA (SUPERFUND) V	VASTEWATER,	RCRA REMEDIATION/CORRECT MEDIAL ACTIVITY WASTEWA	CTIVE TER:
		The state of the s		d that it will) receive waste from remedial activities?
	Yes (complete F.1)		_✓ No	
	Provide a list of sites and	d the requested info	ormation (F.13 - F.15.) for each curre	ent and future site.
F.13.		the site and type o	of facility at which the CERCLA/RCR	A/or other remedial waste originates (or is expected to originate
	in the next five years).			
F.14.	Pollutants. List the haz known. (Attach additional			to be received). Include data on volume and concentration, if
F.15.	Waste Treatment.			
	a. Is this waste treated	(or will it be treated	) prior to entering the treatment work	rs?
	YesNo			
	If yes, describe the tr	reatment (provide in	nformation about the removal efficier	ncy):
	b. Is the discharge (or v	vill the discharge be	e) continuous or intermittent?	
	Continuous			ibe discharge schedule.
			END OF PART I	sse Vd

REFER TO THE APPLICATION OVERVIEW TO DETERMINE WHICH OTHER PARTS OF FORM

2A YOU MUST COMPLETE



SIGNII	FICANT	INDUSTRIAL	USER INFORMATION:
Supply and pro	the follow vide the i	ring information information requ	for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 ested for each SIU.
F.3.	Signific addition	cant Industrial al pages as neces	User Information. Provide the name and address of each SIU discharging to the treatment works. Submit ssary.
Name:		Federal M	ogul Friction Products
	Mailing /	Address: <u>P.O.</u>	Box 3250 Winchester, VA 22604
F.4.	Industr	ial Processes.	Describe all the industrial processes that affect or contribute to the SIU's discharge.
	See At	tached Sheet	
F.5.	Principa SIU's dis		d Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the
	Principal	product(s):	Brake Linings
	Raw mat	• /	Phenolic resins, metallic powders, fiberglass, barium, hydraulic fluid, boiler treatment
F.6.	Flow Ra	ate.	
	a.		rater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in (gpd) and whether the discharge is continuous or intermittent.
		25,0	000 gpd ( continuous orX intermittent)
	b.		stewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the n in gallons per day (gpd) and whether the discharge is continuous or intermittent.
	C.	7,000 gpd sa (	nitary wastewater intermittently, ~2,000 gpd non-contact cooling water gpd continuous orX intermittent)
F.7.	Pretreat	tment Standard	ds. Indicate whether the SIU is subject to the following:
	a.	Local limits	⊠ Yes □ No
	b.	Categorical preti	reatment standards 🔲 Yes 🗵 No
	If subject	to categorical pre	etreatment standards, which category and subcategory?
	***************************************	NATIONAL PROPERTY OF THE PROPE	
F.8.			ment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any erference) at the treatment works in the past three years?
	☐ Yes	⊠ No	If yes, describe each episode.

#### Federal Mogul

Significant User Data
Opequon Water Reclamation Facility
VPDES Permit No. VA0065552

#### F4. Industrial Processes

Raw materials consist of FILLERS (barium sulfate, rubber), FRICTION PARTICLES (fiberglass-80%, steelwool, brass-20%) and BINDERS (Phenolic resins). Raw materials are mixed (4 wet mixers, 5 dry mixers). Pre-formed materials are subjected to pressure, and then materials are subjected to heat and pressure (2500-4500 psi, 185-245 F).

Product is finished and ground to specifications--dust/scrap is collected through a vacuum system. The dust collected by the vacuum system goes to the pelletizing area. The dust is pelletized with concrete and the pellets are landfilled on site. 14 tons/day is collected for landfilling. The waste is stored in totes in a shed until placed in the landfill on one day per week. The landfill remains covered when waste is not being placed into it. The leachate from the landfill is routed to a wet well. The contents of the wet well are pumped to the sanitary sewer main line downstream of the sanitary outfall from the facility.

There are two pumps in place at the landfill leachate pump house, the pumps are alternated.

The brake linings are cleaned in the aqueous degreaser. The aqueous degreaser is not discharged to the sanitary sewer. The water goes through a recycling system; make up water is added as needed. According to the Permittee, there are no metal finishing processes performed on site that would render the aqueous degreaser an ancillary categorical discharge under the metal finishing category.

Adhesive is sprayed on break linings automatically in a hood. There are dry filters to collect overspray. If painting is needed, the same machine is used. The finished product is inspected, packed, printed.

There is a printing shop in a separate building. Impressions Plus is using this print shop at this time. Per the Permittee, there continues to be no printing discharge from this building. Bathrooms in the printing building are connected to the sanitary sewer.

Purge water from groundwater testing is dumped to the leachate wet well and discharged with the leachate. This occurs four times per year, about 300 gallons is generated each time. Olver Inc. performs this testing.

There is a quality control laboratory on site. Sulfuric and nitric acids are used for cleaning. The sulfuric is neutralized using NaOH, the nitric is not dumped.

On occasion, machines may be cleaned--resultant sludge is scooped out in drums and disposed of off site. Only two presses are water cooled at this time. Three compressors use cooling water. Water from the deep well is used for the compressors and heat exchangers. Deep well water is discharged to Abram's Creek and is regulated by a VPDES permit (#0076384).

Water from the hydraulic system is circulated through the presses. It is about 3% hydrolubric oil and 97 % water. This water, cooling water overflows, and leaks from presses go back to the hydraulic system. The water is collected in a tank (est. 2,000 gal.). When the tank is full, the water is discharged to the sanitary sewer.

Boiler blowdown is discharged to the sanitary sewer. Water is softened for the boilers, backwash is discharged to the sanitary sewer.

Acetone is recycled on site, generating non-contact cooling water. Waste acetone that is not recycled, liquid phenolic resin, and all other spent solvents are shipped off site for disposal.

Company of the Compan			

SIGN	IFICANT IND	OUSTRIAL USER INFORMATION:
		information for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and on requested for each SIU.
F.3.		Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit ges as necessary.
	Name:	Sunshine's Pride Dairy, Inc.
	Mailing Addre	ess: 801 North Kent Street, Winchester, VA 22601
F.4.	Industrial F	Processes. Describe all the industrial processes that affect or contribute to the SIU's discharge.
	See Attac	hed Sheet
F.5.	Principal Pridischarge.	oduct(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's
	Principal proc	duct(s): Cheese and Dairy products
	Raw material	(s): Whole milk, cream, cream cheese, salt, banana leaves and rennet
F.6.	Flow Rate.	
		ocess wastewater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in lons per day (gpd) and whether the discharge is continuous or intermittent.
	<u>50</u>	,000 gpd (continuous or _XXintermittent)
		n-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection stem in gallons per day (gpd) and whether the discharge is continuous or intermittent.
	_1	,800 gpd (continuous orXXintermittent)
F.7.	Pretreatme	nt Standards. Indicate whether the SIU is subject to the following:
	a. Loc	cal limits Yes No
	b. Cat	tegorical pretreatment standards 🔲 Yes 🖾 No
	If subject to ca	ategorical pretreatment standards, which category and subcategory?
F.8.		at the Treatment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any property, upsets, interference) at the treatment works in the past three years?
	☐ Yes ⊠	No If yes, describe each episode.
	SANGER CONTROL	
	***************************************	

# Sunshine's Pride Dairy, Inc.


Significant User Data

Opequon Water Reclamation Facility

VPDES Permit No. VA0065552

#### F4. Industrial Processes

Production of natural cheese and cheese products from whole milk and cream. Wastewater generated from plant sanitation, tank cleaning & CIP, and tanker truck cleaning will be collected in pretreatment interceptor and then discharged to the City of Winchester sanitary sewer collection system. Reverse osmosis filtrate from treatment of the cheese whey will also be discharged to the same pretreatment and discharge systems.



SIGN	IFICANT INC	DUSTRIAL USER INFORMATION:
		nformation for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and on requested for each SIU.
F.3.		<b>Industrial User Information.</b> Provide the name and address of each SIU discharging to the treatment works. Submit ges as necessary.
	Name:	Trex Company, Inc.
	Mailing Addre	ess: 3229 Shawnee Drive, Winchester, VA 22602
F.4.	Industrial F	Processes. Describe all the industrial processes that affect or contribute to the SIU's discharge.
	See Attac	hed Sheet
F.5.	Principal Pr discharge.	oduct(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's
		duct(s): wood/plastic composite boards for the construction of decks, picnic tables, benches, ontruction material.
-		(s): Polyethylene scrap (grocery bags, film wrap, etc.) Wood chips are brought to the site and nto sawdust, colorant (carbon black or ferric oxide) are additives
F.6.	Flow Rate.	
	a. Pro gal	ccess wastewater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in lons per day (gpd) and whether the discharge is continuous or intermittent.
	<u>10</u>	0,000 gpd (XX_continuous or intermittent)
		n-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection tem in gallons per day (gpd) and whether the discharge is continuous or intermittent.
	_3	,000 gpd (XX continuous orintermittent)
F.7.	Pretreatme	nt Standards. Indicate whether the SIU is subject to the following:
	a. Loc	al limits Yes No
	b. Cat	egorical pretreatment standards 🔲 Yes 🗵 No
	If subject to ca	ategorical pretreatment standards, which category and subcategory?
	***************************************	
F.8.		t the Treatment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any L, upsets, interference) at the treatment works in the past three years?
	☐ Yes ⊠	No If yes, describe each episode.
	***************************************	

•



### Trex Company, Inc.

Significant User Data
Opequon Water Reclamation Facility
VPDES Permit No. VA0065552

#### F4. Industrial Processes

BUILDING # 1: This facility produces wood/plastic composite boards for construction of decks, picnic tables, benches, etc. Polyethylene scrap (grocery bags, film wrap, etc.) is brought to the site, separated and ground into "fluff". Wood chips are brought to the site and pulverized into sawdust. The wood and "fluff" are weighed, colorant (carbon black or ferric oxide) is added. The melted and mixed ingredients are extruded and conveyed through a cooling water trough. A hose directs a stream of water at the point the board is extruded for quick cooling, then the board travels through the trough. Water is sprayed on the board as it goes through the bath. Chillers have been installed, which have resulted in a decrease in water usage, The contact lines with chillers can recycle, but the problem with the other lines is the high temp of the water at the end of the process. Contact cooling water from cleaning and draining of the cooling troughs and periodic blowdown is discharged to the sanitary sewer. Process and sanitary lines discharge into the same manhole as separate waste streams. The process discharge line includes boiler blowdown and compressor water. Contact cooling water is discharged to the sanitary sewer via the process lines. Compressor condensate is also discharged to the sanitary sewer Boiler blowdown is routed to a flash tank which overflows to the discharge pumps. The blowdown is pumped to the sanitary sewer via the process line. The boiler discharge has time to cool prior to pumping to the sanitary sewer. Last estimates indicate 10 – 15 gal. of boiler blowdown per day.

BUILDING # 2: R&D building. DI water from the Trex testing equipment and pilot-plant equipment is discharged.

**BUILDING # 3**: Bundle cover operation and hollow post extrusion line are housed in this building. White rail co-extrusion lines use the same processes as building #1

**BUILDING # 4**: Processes will be the same as in Building # 1. One line is installed. Boiler blowdown will be discharged to the sanitary sewer.

**BUILDING # 5:** Houses recycled plastic sorting, grading and conversion to polyethylene pellets used in the extrusion lines.

:				
The second secon				
The state of the s				
Access de constitución de parameter de parameter de la constitución de				
11 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2				
The state of the s				
:				

SIGN	IFICANT INDU	STRIAL USER INFORMATION:					
		ormation for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and requested for each SIU.					
F.3.	Significant In additional pages	dustrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit sas necessary.					
	Name:	County of Frederick, Virginia – County Landfill					
	Mailing Address	107 North Kent Street, Winchester, VA 22601					
F.4.	Industrial Pro	ocesses. Describe all the industrial processes that affect or contribute to the SIU's discharge.					
	See Attache	d Sheet					
F.5.	Principal Prod discharge.	uct(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's					
	Principal produc	t(s): Collection of solid wastes generated in Frederick and Clarke Counties and the City of Winchester					
	Raw material(s)	Commercial, Industrial and Municipal solid wastes					
F.6.	Flow Rate.						
	<ul> <li>Process wastewater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in gallons per day (gpd) and whether the discharge is continuous or intermittent.</li> </ul>						
	100,	gpd (continuous orXXintermittent)					
		rocess wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection in gallons per day (gpd) and whether the discharge is continuous or intermittent.					
	0	gpd (intermittent)					
F.7.	Pretreatment	Standards. Indicate whether the SIU is subject to the following:					
	a. Local	limits Yes No					
	b. Categ	orical pretreatment standards 🔲 Yes 🗵 No					
	If subject to categorical pretreatment standards, which category and subcategory?						
F.8.		he Treatment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any upsets, interference) at the treatment works in the past three years?					
	☐ Yes ⊠ N	o If yes, describe each episode.					

# County of Frederick, Virginia - County Landfill


Significant User Data

Opequon Water Reclamation Facility

VPDES Permit No. VA0065552

#### F4. Industrial Processes

The Frederick County Landfill receives solid wastes that are generated from Commercial, Industrial and Municipal sources located in Frederick and Clarke Counties and the City of Winchester. Leachate is generated by liquids in the waste and rainfall on the landfill cells. The liquids migrate through the waste mass and are collected via a network of under-laid piping and stone. The Leachate is then transported via gravity collection system to a pumping station where it is pumped to the on-site pretreatment facility. After pretreatment, the liquid is transferred to the Opequon WRF via force main connected to the Frederick County Sanitation Authority sanitary sewer collection system.



SIGN	IFICANT IND	DUSTRIAL USER INFORMATION:				
		information for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and on requested for each SIU.				
F.3.		Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit ges as necessary.				
	Name:	Kraft Foods Global, Inc.				
	Mailing Addre	ess: 220 Park Center Drive, Winchester, VA 22603				
F.4.	Industrial F	Processes. Describe all the industrial processes that affect or contribute to the SIU's discharge.				
	See Attacl	hed Sheet				
F.5.	Principal Prodischarge.	oduct(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's				
	Principal proc	duct(s): KoolAid, Kool Burst, Capri Sun				
	Raw materials  Product colo	(s): Water, High Fructose Corn Syrup, Fruit Juices & concentrates, Preservatives, Sucrose, Citric acid, ors, product flavors, Polyethylene resin, Mylar foil,				
F.6.	Flow Rate.					
		cess wastewater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in lons per day (gpd) and whether the discharge is continuous or intermittent.				
	<u>28</u> :	0,000 gpd (XX continuous or intermittent)				
		n-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection tem in gallons per day (gpd) and whether the discharge is continuous or intermittent.				
	_7	.500 gpd (_XX_continuous orintermittent)				
F.7.	Pretreatme	nt Standards. Indicate whether the SIU is subject to the following:				
	a. Loc	al limits Yes No				
	b. Cat	egorical pretreatment standards 🔲 Yes 🖾 No				
	If subject to categorical pretreatment standards, which category and subcategory?					
***************************************		·				
F.8.		t the Treatment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any ., upsets, interference) at the treatment works in the past three years?				
	☐ Yes ⊠	No If yes, describe each episode.				
	Desperance and the second					




# Kraft Foods Global, Inc.

Significant User Data
Opequon Water Reclamation Facility
VPDES Permit No. VA0065552

#### F4. Industrial Processes

The Kraft Facility is a Ready-to-Drink beverage production facility. The only process discharge to the sanitary sewer is from overfilled pouches. Filled bottle and pouches are run through a bath to remove stickiness from the outside of the packages. Also, contributing to discharged waste is the CIP for equipment. The wash down procedure for the filling equipment is performed every week, plus on color change days. Lines are rinsed with a hot caustic solution, and the solution is recycled until spent. All of this cleaning water is discharged to the sanitary sewer. Boiler blowdown is also discharged to the sanitary sewer. Incoming water filter backwash is also discharged to the sanitary sewer. Discharge is continuously pH adjusted.



SIGNI	IFICANT IND	USTRIAL USER INFORMATION:
		nformation for each SIU. If more than one SIU discharges to the treatment works, copy questions F.3 through F.8 and in requested for each SIU.
F.3.	•	Industrial User Information. Provide the name and address of each SIU discharging to the treatment works. Submit ges as necessary.
	Name:	O'Sullivan Films, Inc.
	Mailing Addre	ss: 1944 Valley Avenue, Winchester, VA 22601
F,4.	Industrial P	Processes. Describe all the industrial processes that affect or contribute to the SIU's discharge.
	See Attach	ned Sheet
F.5.	Principal Prodischarge.	oduct(s) and Raw Material(s). Describe all of the principal processes and raw materials that affect or contribute to the SIU's
	Principal prod	uct(s): Vinyl sheet material formation; cut to specific size and laminated, painted and/or printed, RCRA wastes
	Raw material( solvent-base	s): Plastic resin, plasticizers, fillers, pigments, stabilizers, and processing aids, water-based adhesives, d products, paints.
F.6.	Flow Rate.	
		cess wastewater flow rate. Indicate the average daily volume of process wastewater discharge into the collection system in ons per day (gpd) and whether the discharge is continuous or intermittent.
	<u>49.</u>	gpd (XX_continuous orintermittent)
		r-process wastewater flow rate. Indicate the average daily volume of non-process wastewater flow discharged into the collection term in gallons per day (gpd) and whether the discharge is continuous or intermittent.
	<u></u>	6,000 gpd (XX_continuous orintermittent)
F.7.	Pretreatmer	nt Standards. Indicate whether the SIU is subject to the following:
	a. Loca	at limits Yes No
	b. Cate	egorical pretreatment standards 🔲 Yes 🖾 No
	If subject to ca	ategorical pretreatment standards, which category and subcategory?
<del>-</del> .8.		t the Treatment Works Attributed to Waste Discharge by the SIU. Has the SIU caused or contributed to any ., upsets, interference) at the treatment works in the past three years?
	☐ Yes 🏻	No If yes, describe each episode.
	0-0000000000000000000000000000000000000	
	101451BACHTO#NNIAAAAAAAHAWACHAAAAAA	



## O'Sullivan Films, Inc.

Significant User Data
Opequon Water Reclamation Facility
VPDES Permit No. VA0065552

#### F4. Industrial Processes

All Plastics wastewater is sent to the sanitary sewer. Non contact cooling water from cooling towers and refrigerated chilling units is discharged to the sanitary system via blowdown and/or system clean-up. Contact cooling water is discharged from dip tanks that are used to directly cool plastic rolls. No chemicals are added to the contact cooling water. Truck and Forklift maintenance is done in an onsite shop. Wastewater from the shop floor drains into a pit to allow solids and oil & grease to separate, and the liquid component is drained to the sanitary sewer.

O'Sullivan Films, Inc. is a producer of RCRA waste. These wastes are not discharged to the sanitary wastewater collection system but are contained on site and shipped off-site for disposal. RCRA wastes are shipped via truck.

Chemtron Corp: acids, isocyonates, mercury

AERC from Frederick County Landfill: universal waste (light bulbs, batteries, computer monitors, etc.)

Recoil: Oil and water

Safety Kleen: waste oils and ;parts cleaner

Potomac Environmental is transport broker for hazardous/non-hazardous materials, oils and oily rags disposed of or recycled off-site.

Southeastern OMNI Chemical and Solvent: solvent glue, ink waste, base glue, paint scrapings, waste solvents and rag waste.

Potomac Environmental: Still bottoms are collected in 55-gallon drums for disposal

Aerosol cans are recycled

Chem Met Services and Environmental Quality: Lab packs

Spirit Services: Currently recycles on site used oil from Banbury mixers; approximately 12 drums per year

	de de desentación de la contractiva de					
	tento de maj frantista ma menajo antes					
	merro era d'Aldrianoma modeles de altra era					
)						
er k.						
of	en e					
A THE TAX PART OF THE TAX PART	abidelisationate manadalidid deleva i televamento a tradition					
	Tool troub at two libraries and a					
	Alla Killist in State constitution for well before					
	an tilden var deligne for fin fin fin fil deligne de deur men					
	Note that makes there have been been been been been been been be					
	even eikeid dässer den men en kantan eine kantan eine kantan kantan kantan eike der district.					

SECTION 3
SLUDGE PERMIT

VPDES PERMIT NUMBER: <u>VA0065552</u>

#### VPDES SEWAGE SLUDGE PERMIT APPLICATION FORM

## SCREENING INFORMATION

This application is divided into sections. Sections A pertain to all applicants. The applicability of Sections B, C and D depend on your facility's sewage sludge use or disposal practices. The information provided on this page will help you determine which sections to fill out.

1.	All applicants must complete Section A (General Information).
2.	Will this facility generate sewage sludge? X Yes No
	Will this facility derive a material from sewage sludge?Yes _X_No
	If you answered Yes to either, complete Section B (Generation Of Sewage Sludge Or Preparation Of A Material Derived From Sewage Sludge).
3.	Will this facility apply sewage sludge to the land?YesXNo
	Will sewage sludge from this facility be applied to the land? Yes X No
	If you answered No to both questions above, skip Section C.
	If you answered Yes to either, answer the following three questions:
-	a. Will the sewage sludge from this facility meet the ceiling concentrations, pollutant concentrations, Class A pathogen reduction requirements and one of the vector attraction reduction requirements 1-8, as identified in the instructions?
	YesNo
	b. Will sewage sludge from this facility be placed in a bag or other container for sale or give-away for application to the land?YesNo
	c. Will sewage sludge from this facility be sent to another facility for treatment or blending?YesNo
	If you answered No to all three, complete Section C (Land Application Of Bulk Sewage Sludge).
	If you answered Yes to a, b or c, skip Section C.
4.	Do you own or operate a surface disposal site? Yes X No
	If Yes, complete Section D (Surface Disposal).

VPDES Sewage Sludge Permit Application Form (2000 Rev.)

Page 1 of 16

VPDES PERMIT NUMBER: VA0065552

#### SECTION A. GENERAL INFORMATION

	All applic	cants must complete this section.
	1. F	Facility Information.
	a b	
	c	. Mailing address:
	d	Street or P.O. Box: 3100 Berryville Pike  City or Town: Winchester State: VA Zip: 22603  Facility location:
		Street or Route #: 3100 Berryville Pike
		County: Frederick County
		City or Town: Winchester State: VA Zip: 22603
	e.	, , <u> </u>
	f.	——————————————————————————————————————
	g h	
	.,	Publicly owned treatment works (POTW) Privately owned treatment works Federally owned treatment works Blending or treatment operation Surface disposal site Other (describe):
2	2. A	pplicant Information. If the applicant is different from the above, provide the following:
	a.	1 1
	b.	Mailing address: P.O. Box 43  Street or P.O. Box:  City or Town: Winchester State: VA _ Zip: 22604
	c.	Contact person: Jesse W. Moffett  Title: Executive Director  Phone: (540) 722-3579
	d.	
		× owneroperator
	e.	Should correspondence regarding this permit be directed to the facility or the applicant? (Check one) facility
3	8. Pe	ermit Information.
	a.	Facility's VPDES permit number (if applicable): VA 0065552
	b. or	List on this form or an attachment, all other federal, state or local permits or construction approvals received applied for that regulate this facility's sewage sludge management practices:
	<u>Pe</u>	ermit Number: Type of Permit
	_	
4		idian Country. Does any generation, freatment, storage, application to land or disposal of sewage sludge from this cility occur in Indian Country?YesXNo If yes, describe:
	_	

VPDES Sewage Sludge Permit Application Form (2000 Rev.)

Page 2 of 16

#### VPDES PERMIT NUMBER: VA0065552

Page 3 of 16

- Topographic Map. Provide a topographic map or maps (or other appropriate maps if a topographic map is unavailable) that shows the following information. Maps should include the area one mile beyond all property boundaries of the facility:
  - Location of all sewage sludge management facilities, including locations where sewage sludge is generated, stored, treated, or disposed.
  - Location of all wells, springs, and other surface water bodies listed in public records or otherwise known to the applicant within 1/4 mile of the property boundaries.
- Line Drawing. Provide a line drawing and/or a narrative description that identifies all sewage sludge processes that will be employed during the term of the permit including all processes used for collecting, dewatering, storing, or treating sewage sludge, the destination(s) of all liquids and solids leaving each unit, and all methods used for pathogen reduction and vector attraction reduction.
- Contractor Information. Are any operational or maintenance aspects of this facility related to sewage sludge generation, treatment, use or disposal the responsibility of a contractor? Yes X No If yes, provide the following for each contractor (attach additional pages if necessary). Name: Mailing address: Street or P.O. Box: City or Town: \_\_\_\_\_State: \_\_\_Zip: \_\_\_\_ Phone: ( ) \_\_\_\_\_ Contractor's Federal, State or Local Permit Number(s) applicable to this facility's sewage sludge:

provided to the applicant and the respective obligations of the applicant and the contractor(s). Pollutant Concentrations. Using the table below or a separate attachment, provide sewage sludge monitoring data for the pollutants which limits in sewage sludge have been established in 9 VAC 25-31-10 et seq. for this facility's expected use or disposal practices. All data must be based on three or more samples taken at least one month apart and must be no more than four and one-half years old.

If the contractor is responsible for the use and/or disposal of the sewage sludge, provide a description of the service to be

POLLUTANT	CONCENTRATION (mg/kg dry weight)	SAMPLE DATE	ANALYTICAL METHOD	DETECTION LEVEL FOR ANALYSIS
Arsenic	See At	ttached Summa	ary Sheet of Sludge	Testing
Cadmium				
Chromium				
Copper				
Lead				
Mercury			4	
Molybdenum				
Nickel				
Selenium				
Zinc				

	Zinc						
9.		is an officer for purpose			plication. Refer to the ir		
	X Section A (General Information)						
	X Section B (Generation of Sewage Sludge or Preparation of a Material Derived from Sewage Sludge)						
	Section C (Land Application of Bulk Sewage Sludge)						
	Section D (Surface Disposal)						
VPDES	Sewage Sludge Permit	Application Form (2000 Rev	:.)		•	Page 3 of 16	


VPDES PERMIT NUMBER: VA0065552

I certify under penalty of law that this document and all attachments were prepared under my direction or supervision in accordance with a system designed to assure that qualified personnel properly gather and evaluate the information submitted. Based on my inquiry of the person or persons who manage the system or those persons directly responsible for gathering the information, the information is, to the best of my knowledge and belief, true, accurate and complete. I am aware that there are significant penalties for submitting false information, including the possibility of fine and imprisonment for knowing violations.

Name and off	idial title	Jesse W.	Moffet	t – Executiv	e Director	- Frede	rick-Wi	ncheste	r Servic	e Authority
Signature	Ku	W		Date Signed _	811710					
Telephone nui	nber <u>(54</u>	0) 722 -	3579		·	· · · · · · · · · · · · · · · · · · ·		The second secon		
				submit any oth fy appropriate p				sess sewa	ge sludge	use or

VPDES Sewage Sludge Permit Application Form (2000 Rev.)

Page 4 of 16



VPDES PERMIT NUMBER: VA0065552

# SECTION B. GENERATION OF SEWAGE SLUDGE OR PREPARATION OF A MATERIAL DERIVED FROM SEWAGE SLUDGE

Complete this section if your facility generates sewage sludge or derives a material from sewage sludge

1.		unt Generated On Site. I dry metric tons per 365-day period generated at your facility: <u>4,875.31</u> dry metric tons
2.	dispo	unt Received from Off Site. If your facility receives sewage sludge from another facility for treatment, use or sal, provide the following information for each facility from which sewage sludge is received. If you receive ge sludge from more than one facility, attach additional pages as necessary.
	a.	Facility name:
	b.	Contact Person:
		Title:
		Phone ( )
	c.	Mailing address:
		Street or P.O. Box
		Street or P.O. Box: City or Town: State: Zip:
	đ.	Facility Address:
	۵.	(not P.O. Box)
	e.	Total dry metric tons per 365-day period received from this facility: dry metric tons
	ψ.	f. Describe, on this form or on another sheet of paper, any treatment processes known to occur at the offsite facility, including blending activities and treatment to reduce pathogens or vector attraction characteristics:
		she facility, faciliting deficing activities and treatment to reduce partiagens of vector attraction characteristics.
3.	Treat	ment Provided at Your Facility.
	a.	Which class of pathogen reduction is achieved for the sewage sludge at your facility?
		X Class A Class B Neither or unknown
	b.	Describe, on this form or another sheet of paper, any treatment processes used at your facility to reduce
		pathogens in sewage sludge: Lime Stabilization of sludge resulting in elevated pH is undertaken
		prior to dewatering of sludge
	c.	Which vector attraction reduction option is met for the sewage sludge at your facility?
		Option 1 (Minimum 38 percent reduction in volatile solids)
		Option 2 (Anaerobic process, with bench-scale demonstration)
		Option 3 (Aerobic process, with bench-scale demonstration)
		Option 4 (Specific oxygen uptake rate for aerobically digested sludge)
		Option 5 (Aerobic processes plus raised temperature)
		X Option 6 (Raise pH to 12 and retain at 11.5)
		Option 7 (75 percent solids with no unstabilized solids)
		Option 8 (90 percent solids with unstabilized solids)
		None or unknown
	ď.	Describe, on this form or another sheet of paper, any treatment processes used at your facility to reduce vector
	u.	
		attraction properties of sewage sludge; Lime Stabilization of sludge resulting in elevated pH is
		undertaken prior to dewatering of sludge
	e.	Describe, on this form or another sheet of paper, any other sewage sludge treatment activities, including
		blending, not identified in a - d above:
4	Dean	nution of Seven as Studen Martine Calling and Ballytont Concentrations, Class A Both sean Begginsternett and
4.		aration of Sewage Sludge Meeting Ceiling and Pollutant Concentrations, Class A Pathogen Requirements and if Vector Attraction Reduction Options 1-8 (EQ Sludge).
		age sludge from your facility does not meet all of these criteria, skip Question 4.)
	a.	Total dry metric tons per 365-day period of sewage sludge subject to this section that is applied to the land: -
		dry metric tons
	b.	Is sewage sludge subject to this section placed in bags or other containers for sale or give-away?
		YesNo
		TANAGAR PARAMANAN PARAMANA

VPDES Sewage Sludge Permit Application Form (2000 Rev.) Page 5 of 16



#### VPDES PERMIT NUMBER: VA0065552

5.		or Give-Away in a Bag or Other Container for Application to the Land.						
	(Comp	(Complete this question if you place sewage sludge in a bag or other container for sale or give-away prior to land application. Skip this question if sewage sludge is covered in Question 4.)						
	a.	Total dry metric tons per 365-day period of sewage sludge placed in a bag or other container at your facility for						
		sale or give-away for application to the land: dry metric tons						
	b.	Attach, with this application, a copy of all labels or notices that accompany the sewage sludge being sold or						
	given	away in a bag or other container for application to the land.						
r	Cile i	Off City for Treatment of Diagrams						
6.		nent Off Site for Treatment or Blending. Lete this question if sewage sludge from your facility is sent to another facility that provides treatment or blending. This question						
	does no	of apply to sewage sludge sent directly to a land application or surface disposal site. Skip this question if the sewage sludge is						
		in Questions 4 or 5. If you send sewage sludge to more than one facility, attach additional sheets as necessary.)						
	a.	Receiving facility name:						
	b.	Facility contact:						
		Title:  Phone: ()  Mailing address:						
		Moiling address.						
	c.	iviaining audit555.						
		Street or P.O. Box:  City or Town:  State:  Zip:  Total dry metric tone per 365 day period of rayrous shudge provided to receiving facility:  dry metric						
	đ.	Total dry metric tons per 365-day period of sewage sludge provided to receiving facility: dry metric						
	G.	tons						
	e.	List, on this form or an attachment, the receiving facility's VPDES permit number as well as the numbers of all						
		other federal, state or local permits that regulate the receiving facility's sewage sludge use or disposal practices:						
		Permit Number: Type of Permit						
	f.	Does the receiving facility provide additional treatment to reduce pathogens in sewage sludge from your						
	i,	facility? Yes No						
		Which class of pathogen reduction is achieved for the sewage sludge at the receiving facility?						
		Class AClass BNeither or unknown						
		Describe, on this form or another sheet of paper, any treatment processes used at the receiving facility to reduce						
		pathogens in sewage sludge:						
	g.	Does the receiving facility provide additional treatment to reduce vector attraction characteristics of the						
		sewage sludge?YesNo						
		Which vector attraction reduction option is met for the sewage sludge at the receiving facility?						
		Option 1 (Minimum 38 percent reduction in volatile solids)						
		Option 2 (Anaerobic process, with bench-scale demonstration)						
		Option 3 (Aerobic process, with bench-scale demonstration)						
		Option 4 (Specific oxygen uptake rate for aerobically digested sludge)						
		Option 5 (Aerobic processes plus raised temperature)						
		Option 6(Raise pH to 12 and retain at 11.5)						
		Option 7 (75 percent solids with no unstabilized solids)						
		Option 8(90 percent solids with unstabilized solids)  None unknown						
		Describe, on this form or another sheet of paper, any treatment processes used at the receiving facility to reduce						
		vector attraction properties of sewage sludge:						
	h.	Does the receiving facility provide any additional treatment or blending not identified in for g above?						
	13.	Yes No						
		If yes, describe, on this form or another sheet of paper, the treatment processes not identified in for g above:						
		, , , , , , , , , , , , , , , , , , ,						
	i.	If you answered yes to f., g or h above, attach a copy of any information you provide to the receiving facility to						
		comply with the "notice and necessary information" requirement of 9 VAC 25-3 1-530.G.						

VPDES Sewage Sludge Permit Application Form (2000 Rev.)

Page 6 of 16

FACI	LITY NA	ME: OPEQUON WATER RECLAMATION FACILITY	VPDES PERMIT NUMBER: <u>VA0065552</u>
	j.	Does the receiving facility place sewage sludge from your facilit away for application to the land?YesNo If yes, provide a copy of all labels or notices that accompany the	
	k.	Will the sewage sludge be transported to the receiving facility in for such purposes? Yes No. If no, provide description as the sewage sludge to the receiving facility.	a truck-mounted watertight tank normally used
		Show the haul route(s) on a location map or briefly describe the week and the times of the day sewage sludge will be transported.	
7.	(Complet	Application of Bulk Sewage Sludge. ete Question 7.a if sewage sludge from your facility is applied to the land, unless te Question 7.b, c & d only If you are responsible for land application of sewage	sludge.)
	a. b.	Total dry metric tons per 365-day period of sewage sludge applied Do you identify all land application sites in Section C of this applied If no, submit a copy of the Land Application Plan (LAP) with this accordance with the instructions).	lication?YesNo
	c.	Are any land application sites located in States other than Virgini If yes, describe, on this form or on another sheet of paper, how you where the land application sites are located. Provide a copy of the	ou notify the permitting authority for the States
	d.	Attach a copy of any information you provide to the owner or lea comply with the "notice and necessary" information requirement may be obtained in Appendix IV).	
8.		e Disposal.  ete Question S if sewage sludge from your facility is placed on a surface disposal  Total dry metric tons per 365-day period of sewage sludge from  sites: dry metric tons	
	b.	Do you own or operate all surface disposal sites to which you sen  Yes No  If no, answer questions - g for each surface disposal site that you studge to more than one surface disposal site, attach additional pa	do not own or operate. If you send sewage
	c.` d.	Site name or number: Contact person: Title:	
	e.	Phone: ( )  Contact is:Site OwnerSite operator  Mailing address.  Street or P.O. Box:  City or Town:State: Zip:	
	f.	Total dry metric tons per 365-day period of sewage sludge from y site:  dry metric tons	our facility placed on this surface disposal
	g.	List, on this form or an attachment, the surface disposal site VPD all other federal, state or local permits that regulate the sewage sludisposal site:	DES permit number as well as the numbers of udge use or disposal practices at the surface
		Permit Number: Type of Permit	
9.	Incinera	ation. te Question 9 if sewage sludge from your facility is tired in a sewage sludge inci	nerator)
	a.	Total dry metric tons per 365-day period of sewage sludge from y incinerator: dry metric tons	

VPDES Sewage Sludge Permit Application Form (2000 Rev.)


Page 7 of 16

	YesNo
	If no, answer questions c - g for each sewage sludge incinerator that you do not own or operate. If you send sewage sludge to more than one sewage sludge incinerator, attach additional pages as necessary.
c.	Incinerator name or number:
d.	Contact person:
	Title:
	Phone: ( )
	Contact is:Incinerator OwnerIncinerator Operator
e.	Mailing address.
	Street or P.O. Box:
	Street or P.O. Box:  City or Town:  State:  Zip:
f.	total dry metric tons per 363-day period of sewage studge from your facility fired in this sewage studge
	incinerator: dry metric tons
g.	List on this form or an attachment the numbers of all other federal, state or local permits that regulate the firing
	of sewage sludge at this incinerator:
	Permit Number: Type of Permit
	sal in a Municipal Solid Waste Landfill.
(Comp	lete Question 10 If sewage sludge from your facility is placed on a municipal solid waste landfill. Provide the following Information for
solid w	unicipal solid waste landfill on which sewage sludge from your facility is placed. If sewage sludge is placed on more than one municipa aste landfill, attach additional pages as necessary.)
	Landfill name: Frederick County Regional Landfill
D.	Contact person: Mr. Steven Frye
	Title: Landfill Manager
	Phone: (540) 665-5658
	Contact is:Landfill OwnerXLandfill Operator
c.	Mailing address. Street or P.O. Box: 280 Landfill Road
	City or Town: Winchester State: VA Zip: 22602
d.	Landfill location.
<del>-</del>	Street or Route #: Located off of Sulfur Spring Road
	County: Frederick
	City or Town: Winchester State: VA Zip: 22602
e.	Total dry metric tons per 365-day period of sewage sludge placed in this municipal solid waste landfill:
	4,875.31 dry metric tons
f.	List, on this form or an attachment, the numbers of all federal, state or local permits that regulate the operation
	of this municipal solid waste landfill:
	<u>Permit Number:</u> <u>Type of Permit</u>
	529Solid Waste
	VRO81312 Air
	VA0088471 Wastewater
α	Does sewage sludge meet applicable requirements in the Virginia Solid Waste Management Regulation, 9
5.	VAC 20-80-10 et seq., concerning the quality of materials disposed in a municipal solid waste landfill?
1.	X Yes No
H.	Does the municipal solid waste landfill comply with all applicable criteria set forth in the Virginia Solid Waste
	Management Regulation, 9 VAC 20-80-10 et seq.? X Yes No
1.	Will the vehicle bed or other container used to transport sewage sludge to the municipal solid waste landfill be
	watertight and covered? X Yes No
	Show the haul route(s) on a location map or briefly describe the route below and indicate the days of the week
	and time of the day sewage sludge will be transported. See Attached Routing Map
	d. e. f. g. Dispo (Comp each m solid w a. b. c. d.

VPDES Sewage Sludge Permit Application Form (2000 Rev.)

Page 8 of 16

# Opequon Water Reclamation Facility - Sludge Disposal Route



### Sludge Hauling Route

- Exit Opequon Facility onto Route 7 West
   Turn left onto Greenwood Road (SR 656)
   Follow Greenwood Road to intersection with Sulphur Spring Road (SR 655)
   Turn left on Sulphur Spring Road to Landfill Road. Entrance to Frederick County Landfill.

### Frederick-Winchester Service Authority

Facility: Opequon Water Reclamation Facility
Permit Number: VAL0065552

## Sludge Disposal - January 1, 2009 to December 31, 2009

		ei	0.74%	<b>14,645.08</b> 108.80	Prior Yr.
4,422.88		4,875.31	33.12%	14,753.88	Totals
293.98	0.9072	324.05	30.60%	1,058.99	December
320.74	0.9072	353.55	34.20%	1,033.77	November
347.05	0.9072	382.55	33.80%	1,131.81	October
371.95	0.9072	410.00	34.90%	1,174.79	September
312.98	0.9072	345.00	34.60%	997.10	August
360.20	0.9072	397.04	34.80%	1,140.93	July
411.15	0.9072	453.21	35.30%	1,283.87	June
458.54	0.9072	505.45	32.70%	1,545.72	May
400.91	0.9072	441.92	32.10%	1,376.71	April
481.78	0.9072	531.07	31.50%	1,685.93	March
308.26	0.9072	339.79	31.10%	1,092.57	February
355.33	0.9072	391.68	31.80%	1,231.69	January
Metric dry tons	conv.	dry tons	% solids	wet tons	Month

### 5 Year Sludge Analysis Summary

Pollutant	2006	2007	2008	2009	2010	5 Year Avg.
Arsenic	1.45	2.00	2.17	24.01	4.58	7.59
Cadmium	1.67	2.83	1.00	1.57	1.59	1.74
Chromium	34.50	33.00	30.83	23.70	27.70	29.89
Copper	260.33	284.33	269.17	265.98	279.25	271.10
Lead	23.60	12.50	9.00	8.52	6.88	11.52
Mercury	0.40	0.43	0.42	0.23	0.07	0.32
Molybdenum	8.83	8.40	6.00	5.22	3.85	6.31
Nickel	24.17	21.50	19.33	15.87	18.05	19.77
Selenium	1.73	1.33	2.07	7.56	5.53	3.46
Zinc	238.83	286.33		210.29	240.25	239.79
		Concen	trations (	mg/kg di	y weight	:)

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.3	January 24, 2006	SW 846-7061A
Cadmium	1	January 24, 2006	SW 846-6010B
Chromium	34	January 24, 2006	SW 846-6010B
Copper	197	January 24, 2006	SW 846-6010B
Lead		January 24, 2006	SW 846-6010B
Mercury	0.21	January 24, 2006	SW 846-7471A
Molybdenum	8	January 24, 2006	SW 846-6010B
Nickel	20	January 24, 2006	SW 846-6010B
Selenium	1.78	January 24, 2006	SW 846-7741A
Zinc	152	January 24, 2006	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.5	April 27, 2006	SW 846-7061A
Cadmium	1	April 27, 2006	SW 846-6010B
Chromium	26	April 27, 2006	SW 846-6010B
Copper	291	April 27, 2006	SW 846-6010B
Lead	14	April 27, 2006	SW 846-6010B
Mercury	0.5	April 27, 2006	SW 846-7471A
Molybdenum	7	April 27, 2006	SW 846-6010B
Nickel	24	April 27, 2006	SW 846-6010B
Selenium	2.1	April 27, 2006	SW 846-7741A
Zinc	279	April 27, 2006	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	0.8	May 24, 2006	SW 846-7061A
Cadmium	1	May 24, 2006	SW 846-6010B
Chromium	25	May 24, 2006	SW 846-6010B
Copper	205	May 24, 2006	SW 846-6010B
Lead	39	May 24, 2006	SW 846-6010B
Mercury	0.2	May 24, 2006	SW 846-7471A
Molybdenum	6	May 24, 2006	SW 846-6010B
Nickel	16	May 24, 2006	SW 846-6010B
Selenium	1.1	May 24, 2006	SW 846-7741A
Zinc	156	May 24, 2006	SW 846-6010B

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.4	July 25, 2006	SW 846-7061A
Cadmium	2.0	July 25, 2006	SW 846-6010B
Chromium	40	July 25, 2006	SW 846-6010B
Copper	273	July 25, 2006	SW 846-6010B
Lead	21	July 25, 2006	SW 846-6010B
Mercury	0.5	July 25, 2006	SW 846-7471A
Molybdenum	9	July 25, 2006	SW 846-6010B
Nickel	23	July 25, 2006	SW 846-6010B
Selenium	1.4	July 25, 2006	SW 846-7741A
Zinc	287	July 25, 2006	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.8	September 12, 2006	SW 846-7061A
Cadmium	3	September 12, 2006	SW 846-6010B
Chromium	47	September 12, 2006	SW 846-6010B
Copper	322	September 12, 2006	SW 846-6010B
Lead	29	September 12, 2006	SW 846-6010B
Mercury	0.4	September 12, 2006	SW 846-7471A
Molybdenum	12	September 12, 2006	SW 846-6010B
Nickel	33	September 12, 2006	SW 846-6010B
Selenium	1.3	September 12, 2006	SW 846-7741A
Zinc	368	September 12, 2006	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.9	November 14, 2006	SW 846-7061A
Cadmium	2.0	November 14, 2006	SW 846-6010B
Chromium	35	November 14, 2006	SW 846-6010B
Copper	274	November 14, 2006	SW 846-6010B
Lead	15	November 14, 2006	SW 846-6010B
Mercury	0.6	November 14, 2006	SW 846-7471A
Molybdenum	11	November 14, 2006	SW 846-6010B
Nickel	29	November 14, 2006	SW 846-6010B
Selenium	2.7	November 14, 2006	SW 846-7741A
Zinc	191	November 14, 2006	SW 846-6010B

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.7	January 30, 2007	SW 846-7061A
Cadmium	1.0	January 30, 2007	SW 846-6010B
Chromium	34	January 30, 2007	SW 846-6010B
Copper	232	January 30, 2007	SW 846-6010B
Lead	5	January 30, 2007	SW 846-6010B
Mercury	0.4	January 30, 2007	SW 846-7471A
Molybdenum	8	January 30, 2007	SW 846-6010B
Nickel	28	January 30, 2007	SW 846-6010B
Selenium	1.1	January 30, 2007	SW 846-7741A
Zinc	214	January 30, 2007	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.7	March 22, 2007	SW 846-7061A
Cadmium	3.0	March 22, 2007	SW 846-6010B
Chromium	42	March 22, 2007	SW 846-6010B
Copper	291	March 22, 2007	SW 846-6010B
Lead	26	March 22, 2007	SW 846-6010B
Mercury	0.4	March 22, 2007	SW 846-7471A
Molybdenum	11	March 22, 2007	SW 846-6010B
Nickel	31	March 22, 2007	SW 846-6010B
Selenium	1.9	March 22, 2007	SW 846-7741A
Zinc	242	March 22, 2007	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.2	May 17, 2007	SW 846-7061A
Cadmium	2.0	May 17, 2007	SW 846-6010B
Chromium	44	May 17, 2007	SW 846-6010B
Copper	321	May 17, 2007	SW 846-6010B
Lead	17	May 17, 2007	SW 846-6010B
Mercury	0.5	May 17, 2007	SW 846-7471A
Molybdenum	12	May 17, 2007	SW 846-6010B
Nickel	23	May 17, 2007	SW 846-6010B
Selenium	1.8	May 17, 2007	SW 846-7741A
Zinc	420	May 17, 2007	SW 846-6010B

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.4	July 23, 2007	SW 846-7061A
Cadmium	1	July 23, 2007	SW 846-6010B
Chromium	23	July 23, 2007	SW 846-6010B
Copper	300	July 23, 2007	SW 846-6010B
Lead	10	July 23, 2007	SW 846-6010B
Mercury	0.5	July 23, 2007	SW 846-7471A
Molybdenum	5	July 23, 2007	SW 846-6010B
Nickel	15	July 23, 2007	SW 846-6010B
Selenium	2.1	July 23, 2007	SW 846-7741A
Zinc	295	July 23, 2007	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.9	September 11, 2007	SW 846-7061A
Cadmium	5	September 11, 2007	SW 846-6010B
Chromium	31	September 11, 2007	SW 846-6010B
Copper	336	September 11, 2007	SW 846-6010B
Lead	10	September 11, 2007	SW 846-6010B
Mercury	0.4	September 11, 2007	SW 846-7471A
Molybdenum	6	September 11, 2007	SW 846-6010B
Nickel	18	September 11, 2007	SW 846-6010B
Selenium	0.1	September 11, 2007	SW 846-7741A
Zinc	304	September 11, 2007	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.1	November 13, 2007	SW 846-7061A
Cadmium	5	November 13, 2007	SW 846-6010B
Chromium	24	November 13, 2007	SW 846-6010B
Copper	226	November 13, 2007	SW 846-6010B
Lead	7	November 13, 2007	SW 846-6010B
Mercury	0.4	November 13, 2007	SW 846-7471A
Molybdenum	<5	November 13, 2007	SW 846-6010B
Nickel	14	November 13, 2007	SW 846-6010B
Selenium	1.	November 13, 2007	SW 846-7741A
Zinc	243	November 13, 2007	SW 846-6010B


Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.3	January 2, 2008	SW 846-7061A
Cadmium	1	January 2, 2008	SW 846-6010B
Chromium	30	January 2, 2008	SW 846-6010B
Copper	209	January 2, 2008	SW 846-6010B
Lead	6	January 2, 2008	SW 846-6010B
Mercury	0.4	January 2, 2008	SW 846-7471A
Molybdenum	5	January 2, 2008	SW 846-6010B
Nickel	16	January 2, 2008	SW 846-6010B
Selenium	1	January 2, 2008	SW 846-7741A
Zinc	179	January 2, 2008	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.0	March 5, 2008	SW 846-7061A
Cadmium	1	March 5, 2008	SW 846-6010B
Chromium	26	March 5, 2008	SW 846-6010B
Copper	207	March 5, 2008	SW 846-6010B
Lead	5	March 5, 2008	SW 846-6010B
Mercury	0.4	March 5, 2008	SW 846-7471A
Molybdenum	5	March 5, 2008	SW 846-6010B
Nickel	15	March 5, 2008	SW 846-6010B
Selenium	1	March 5, 2008	SW 846-7741A
Zinc	160	March 5, 2008	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.2	May 2, 2008	SW 846-7061A
Cadmium	1	May 2, 2008	SW 846-6010B
Chromium	31	May 2, 2008	SW 846-6010B
Copper	229	May 2, 2008	SW 846-6010B
Lead	15	May 2, 2008	SW 846-6010B
Mercury	0.5	May 2, 2008	SW 846-7471A
Molybdenum	5	May 2, 2008	SW 846-6010B
Nickel	19	May 2, 2008	SW 846-6010B
Selenium	1.1	May 2, 2008	SW 846-7741A
Zinc	206	May 2, 2008	SW 846-6010B

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.6	July 1, 2008	SW 846-7061A
Cadmium	1.0	July 1, 2008	SW 846-6010B
Chromium	27	July 1, 2008	SW 846-6010B
Copper	259	July 1, 2008	SW 846-6010B
Lead	10	July 1, 2008	SW 846-6010B
Mercury	0.4	July 1, 2008	SW 846-7471A
Molybdenum	5	July 1, 2008	SW 846-6010B
Nickel	19	July 1, 2008	SW 846-6010B
Selenium	1.7	July 1, 2008	SW 846-7741A
Zinc	229	July 1, 2008	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.6	October 8, 2008	SW 846-7061A
Cadmium	1	October 8, 2008	SW 846-6010B
Chromium	39	October 8, 2008	SW 846-6010B
Copper	318	October 8, 2008	SW 846-6010B
Lead	5	October 8, 2008	SW 846-6010B
Mercury	0.4	October 8, 2008	SW 846-7471A
Molybdenum	10	October 8, 2008	SW 846-6010B
Nickel	25	October 8, 2008	SW 846-6010B
Selenium	5.2	October 8, 2008	SW 846-7741A
Zinc	252	October 8, 2008	SW 846-6010B
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.3	November 25, 2008	SW 846-7061A
Cadmium	1	November 25, 2008	SW 846-6010B
Chromium	32	November 25, 2008	SW 846-6010B
Copper	393	November 25, 2008	SW 846-6010B
Lead	13	November 25, 2008	SW 846-6010B
Mercury	0.4	November 25, 2008	SW 846-7471A
Molybdenum	6	November 25, 2008	SW 846-6010B
Nickel	22	November 25, 2008	SW 846-6010B
Selenium	2.4	November 25, 2008	SW 846-7741A
Zinc	344	November 25, 2008	SW 846-6010B

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	1.5	January 5, 2009	SW 846-7061A
Cadmium	1	January 5, 2009	SW 846-6010B
Chromium	26	January 5, 2009	SW 846-6010B
Copper	283	January 5, 2009	SW 846-6010B
Lead	6	January 5, 2009	SW 846-6010B
Mercury	0.4	January 5, 2009	SW 846-7471A
Molybdenum	5	January 5, 2009	SW 846-6010B
Nickel	15	January 5, 2009	SW 846-6010B
Selenium	3.7	January 5, 2009	SW 846-7741A
Zinc	236	January 5, 2009	SW 846-6010B
Pollutant	Concentration (ug/g dry weight)	Sample Date	Analytical Method
Arsenic	46	March 3, 2009	SW 846-60
Cadmium	2	March 3, 2009	SW 846-60
Chromium	24.9	March 3, 2009	SW 846-60
Copper	258	March 3, 2009	SW 846-60
Lead	4	March 3, 2009	SW 846-60
Mercury	0.215	March 3, 2009	SW 846-60
Molybdenum	5.56	March 3, 2009	SW 846-60
Nickel	15.2	March 3, 2009	SW 846-60
Selenium	4	March 3, 2009	SW 846-60
Zinc	151	March 3, 2009	SW 846-60
Pollutant	Concentration (ug/g dry weight)	Sample Date	Analytical Method
Arsenic	52.5	April 6, 2009	SW 846-60
Cadmium	2	April 6, 2009	SW 846-60
Chromium	21.9	April 6, 2009	SW 846-60
Copper	257	April 6, 2009	SW 846-60
Lead	7.98	April 6, 2009	SW 846-60
Mercury	0.317	April 6, 2009	SW 846-60
Molybdenum	5.33	April 6, 2009	SW 846-60
Nickel	13.9	April 6, 2009	SW 846-60
Selenium	4	April 6, 2009	SW 846-60
Zinc	221	April 6, 2009	SW 846-60

Pollutant	Concentration (ug/g dry weight)	Sample Date	Analytical Method	
Arsenic	29.9	May 5, 2009	SW 846-60	
Cadmium	2	May 5, 2009	SW 846-60	
Chromium	11.8153	May 5, 2009	SW 846-60	
Copper	4.83	May 5, 2009	SW 846-60	
Lead	4.83	May 5, 2009	SW 846-60	
Mercury	0.198	May 5, 2009	SW 846-60	
Molybdenum	4	May 5, 2009	SW 846-60	
Nickel	9.48	May 5, 2009	SW 846-60	
Selenium	20	May 5, 2009	SW 846-60	
Zinc	104	May 5, 2009	SW 846-60	
Pollutant	Concentration (ug/g dry weight)	Sample Date	Analytical Method	
Arsenic	29.8	July 6, 2009	SW 846-60	
Cadmium	2	July 6, 2009	SW 846-60	
Chromium	24.3	July 6, 2009	SW 846-60	
Copper	364	July 6, 2009	SW 846-60	
Lead	21.6	July 6, 2009	SW 846-60	
Mercury	0.318	July 6, 2009	SW 846-60	
Molybdenum	7.74	July 6, 2009	SW 846-60	
Nickel	16	July 6, 2009	SW 846-60	
Selenium	17.2	July 6, 2009	SW 846-60	
Zinc	208	July 6, 2009	SW 846-60	
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method	
Arsenic	4.5	September 22, 2009	SW 846-60	
Cadmium	1.3	September 22, 2009	SW 846-60	
Chromium	27.6	September 22, 2009	SW 846-60	
Copper	314	September 22, 2009	SW 846-60	
Lead	5.7	September 22, 2009	SW 846-60	
Mercury	0.063	September 22, 2009	SW 846-60	
Molybdenum	4.1	September 22, 2009	SW 846-60	
Nickel	19.2	September 22, 2009	SW 846-60	
Selenium	4.0	September 22, 2009	SW 846-60	
Zinc	274	September 22, 2009	SW 846-60	

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	3.9	November 3, 2009	SW 846-60
Cadmium	0.71	November 3, 2009	SW 846-60
Chromium	29.4	November 3, 2009	SW 846-60
Copper	381	November 3, 2009	SW 846-60
Lead	9.5	November 3, 2009	SW 846-60
Mercury	0.09	November 3, 2009	SW 846-60
Molybdenum	4.8	November 3, 2009	SW 846-60
Nickel	22.3	November 3, 2009	SW 846-60
Selenium	0.0	November 3, 2009	SW 846-60
Zinc	278	November 3, 2009	SW 846-60



Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	4.9	January 5, 2010	EPA 6010
Cadmium	1.6	January 5, 2010	EPA 6010
Chromium	29.1	January 5, 2010	EPA 6010
Copper	276	January 5, 2010	EPA 6010
Lead	4.6	January 5, 2010	EPA 6010
Mercury	0.038	January 5, 2010	EPA 6010
Molybdenum	4.3	January 5, 2010	EPA 6010
Nickel	19.3	January 5, 2010	EPA 6010
Selenium	7.0	January 5, 2010	EPA 6010
Zinc	187	January 5, 2010	EPA 6010
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	3.0	March 1, 2010	EPA 6010
Cadmium	2.3	March 1, 2010	EPA 6010
Chromium	26.7	March 1, 2010	EPA 6010
Copper	297	March 1, 2010	EPA 6010
Lead	6.1	March 1, 2010	EPA 6010
Mercury	0.08	March 1, 2010	EPA 6010
Molybdenum	4.1	March 1, 2010	EPA 6010
Nickel	17.8	March 1, 2010	EPA 6010
Selenium	4.5	March 1, 2010	EPA 6010
Zinc	212	March 1, 2010	EPA 6010
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	2.7	May 4, 2010	EPA 6010
Cadmium	1.9	May 4, 2010	EPA 6010
Chromium	32.9	May 4, 2010	EPA 6010
Copper	229	May 4, 2010	EPA 6010
Lead	7.0	May 4, 2010	EPA 6010
Mercury		May 4, 2010	EPA 6010
Molybdenum	4.2	May 4, 2010	EPA 6010
Nickel	22	May 4, 2010	EPA 6010
Selenium	5.1	May 4, 2010	EPA 6010
Zinc	216	May 4, 2010	EPA 6010

Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic	7.7	July 1, 2010	EPA 6010
Cadmium	0.56	July 1, 2010	EPA 6010
Chromium	22.1	July 1, 2010	EPA 6010
Copper	315	July 1, 2010	EPA 6010
Lead	9.8	July 1, 2010	EPA 6010
Mercury	0.095	July 1, 2010	EPA 6010
Molybdenum	2.8	July 1, 2010	EPA 6010
Nickel	13.1	July 1, 2010	EPA 6010
Selenium	ND	July 1, 2010	EPA 6010
Zinc	346	July 1, 2010	EPA 6010
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic			EPA 6010
Cadmium			EPA 6010
Chromium	5.4		EPA 6010
Copper		s 	EPA 6010
Lead			EPA 6010
Mercury	9.		EPA 6010
Molybdenum			EPA 6010
Nickel			EPA 6010
Selenium			EPA 6010
Zinc			EPA 6010
Pollutant	Concentration (mg/kg dry weight)	Sample Date	Analytical Method
Arsenic			EPA 6010
Cadmium			EPA 6010
Chromium			EPA 6010
Copper			EPA 6010
Lead			EPA 6010
Mercury			EPA 6010
Molybdenum			EPA 6010
Nickel			EPA 6010
Selenium			EPA 6010
Zinc	P		EPA 6010

### SECTION 4

OTHER FORMS

(VPDES PERMIT APPLICATION ADDENDUM,

PERMIT BILLING FORM,

PUBLIC NOTICE BILLING INFORMATION FORM)

### VPDES Permit Application Addendum

1. Entity to whom the permit is to be issued: <u>Frederick-Winchester Service Authority</u> Who will be legally responsible for the wastewater treatment facilities and compliance with the permit? This may or may not be the facility or property owner.
2. Is this facility located within city or town boundaries? $Y/N$
3. What is the tax map parcel number for the land where this facility is located? 56-A-19
4. For the facility to be covered by this permit, how many acres will be disturbed during the next five years due to new construction activities? $N/A$
5. ALL FACILITIES: What is the design average flow of this facility? 12.6 MGD Industrial facilities: What is the max. 30-day avg. production level (include units)?
In addition to the above design flow or production level, should the permit be written with limits for any other discharge flow tiers or production levels? YN
If "Yes", please specify the other flow tiers (in MGD) or production levels:  Please consider: Is your facility design flow considerably greater than your current flow? Do you plan to expand operations during the next five years?
6. Nature of operations generating wastewater:  Nature of wastewater is both domestic and industrial in source
Number of private residences to be served by the wastewater treatment facilities:01-49 × 50 or more
28 % of flow from non-domestic connections/sources
7. <b>Mode of discharge</b> : X Continuous Intermittent Seasonal Describe frequency and duration of intermittent or seasonal discharges:
8. Identify the characteristics of the receiving stream at the point just above the facility's discharge point:
Permanent stream, never dry
Intermittent stream, usually flowing, sometimes dry
Ephemeral stream, wet-weather flow, often dry
Effluent-dependent stream, usually or always dry
Lake or pond at or below the discharge point
Other:
9. Approval Date(s): O & M Manual April 22, 2002 Sludge/Solids Management Plan February 24, 1988
Have there been any changes in your operations or procedures since the above approval dates? Y (N)
1/9

### PUBLIC NOTICE BILLING INFORMATION

Agent/Department to be billed:	Frederick-Winchester Service Authority
Owner:	
Agent/Department Address:	P.O Box 43
	Winchester, Virginia
	22604
Agent's Telephone No.:	(540) 722-3579
Printed Name:	Jesse W. Moffett
Authorizing Agent – Signature:	In units
Date:	8/12/10

Opequon WRF

VPDES Permit No. VA0065552

**Attention Permittee**: Please complete the above information and return this form with your application to Trevor Wallace, DEQ-Valley Regional Office, P.O. Box 3000, Harrisonburg, Virginia 22801.

### VPDES/VPA Permit Billing Information Form for Annual Maintenance Fee

Facility Name:	Opequon Water Reclamation Facility	
Permit Number:	VA0065552	
Tax Payer ID (Federal Identification Number):	54-1035792	
Social Security Number if no Tax Payer ID:		
	Frederick-Winchester Service Authority	
Owner Address:	P.O. Box 43	
· ·	Winchester, VA 22604	
Billing Contact Name:		
Title:	Executive Director	
Phone Number:	(540) 722-3579	
E-Mail Address:	jmoffett@fredwin.com	

U:\WATER PERMITS\APPLICATION FORMS\Permit Billing Information Form.doc